

Orbiter®

DMX Mode Specification V5.0

LIGHTING - TECHNICAL INFORMATION

L5.0037960

07 / 2022

L03936

Revision History

Date	L-Number	Page	Changes	Sign
26.08.2020	-	-	First Release	PM-SW
15.09.2020	L03616	13 - 22 26 - 27 43	Gels: 16 Bit Values added Sources: 16 Bit Values added Ultimate: 16 Bit Values at Color Mode Parameters " Gel Selection" and "Source Matching" added	PM-SW
20.04.2021	L03936	12 13 - 22	Gel Selection Modes: 16 Bit - Channel 05/06/07/08 - Correction 16 Bit Value "-" Gels table: 8 Bit values changed, 16 Bit values for Ultimate Mode corrected	PM-SW
21.06.2021		25	Source Matching Modes: 16 Bit - Channel 03/04 - Correction 16 Bit Value "-"	
25.05.2022		all	Change of parameter names: "Frequency" --> "Speed"; "Speed" --> "Sequence" -->; "Sync" --> "Trigger"	
		all	General change of mode numbers	
		all	Beam control (Zoom / Focus / Reserved) channels added to each mode	
		all	Renaming of "Reduced Channels" to "Operation"	
		all	Operation Channel extended about "Color Sensor" and "Sync"	
		all	Possibility to activate/deactivate Operation Channel	
		all	More Gels available	
		all	Integration of CCT & RGBACL Mode (previously mode 1 and 6) in RGBACL Mode	

© 2018 – 2020 Arnold & Richter Cine Technik GmbH & Co. Betriebs KG.

All rights reserved. Information subject to change without notice. ARRI and all affiliated companies disclaim liability for any injury, damage, direct or indirect loss, consequential or economic loss or any other loss occasioned by the use of, inability to use or reliance on the information contained in this document.

No part of this document may be used for distribution, reproduction, transmission, transcription, storage in a data retrieval system, or translated into any language in any form by any means without the prior written permission of ARRI. If you are downloading files from our web pages for your personal use, make sure to check for updated versions. ARRI cannot take any liability whatsoever for downloaded files, as technical data are subject to change without notice.

ARRI, the ARRI Logo, ARRIMAX, ARRISUN, EB**UOS**, L-Series, MAX Technology, M-Series, Orbiter, POCKETPAR, Quick Lighting Mount, True Blue, SkyPanel, SKYPANEL, T 12 and T 24 are registered trademarks of Arnold & Richter Cine Technik GmbH & Co. Betriebs KG.

Revision History 2

Table of Content 3

Green / Magenta Point & Favorite Channel 4

Parameter Allocation 5

DMX Protocol Specification

 CCT Modes 1 & 2 6

 HSI Modes 3 & 4 8

 x, y Coordinates Modes 5 & 6 10

 Gel Selection Modes 7 & 8 12

 Source Matching Modes 9 & 10 25

 Lighting Effects Modes 11 & 12 29

 RGBACL Modes 13 & 14 36

 CCT & HSI Modes 15 & 16 39

 Ultimate Modes 17 & 18 41

Equations for Conversion 47



Green / Magenta Point - Average Equivalents

Setting	Rosco #
Full -Green	3308
1/2 -Green	3313
1/4 -Green	3314
1/8 -Green	3318
Full +Green	3304
1/2 +Green	3315
1/4 +Green	3316
1/8 +Green	3317

Favorite Channel - DMX Value Allocation

DMX Channel	Parameter Name	Function	Value 8 Bit		% 8 Bit		% 8 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
Depending on DMX Mode	Favorites	No Effect	0	9	-	-	1*	-	-	-
	User Defined Favorites	Favorite 01	10	-	-	-	-	-	-	-
		Favorite 02	11	-	-	-	-	-	-	-
		Favorite 03	12	-	-	-	-	-	-	-
		Favorite 04	13	-	-	-	-	-	-	-
		Favorite 05	14	-	-	-	-	-	-	-
		Favorite 06	15	-	-	-	-	-	-	-
		-	-	-	-	-	-	-
		Favorite 246	255	-	-	-	-	-	-	-

* Providing a percentage less than "1" is not possible



Extended Color Control (ECC)

Parameter	Channel Layout		
	8 Bit	16 Bit	
		Hi	Lo
Warmer / Cooler	I + 1	I + 1	I + 2
Saturate / Desaturate	I + 2	I + 3	I + 4
+ Red / - Red	I + 3	I + 5	I + 6
+ Green / - Green	I + 4	I + 7	I + 8
+ Blue / - Blue	I + 5	I + 9	I + 10
+ Cyan / - Cyan	I + 6	I + 11	I + 12
+ Magenta / - Magenta	I + 7	I + 13	I + 14
+ Yellow / - Yellow	I + 8	I + 15	I + 16

I = Highest channel number of selected mode

Operation

Parameter	Channel Layout		
	8 Bit	16 Bit	
		Hi	Lo
Fan Control	ECC OFF: I + 1	-	-
	ECC ON: I + 8 + 1	-	-
Favorites	ECC OFF: I + 2	-	-
	ECC ON: I + 8 + 2	-	-
Light Strobe ²	ECC OFF: I + 3	-	-
	ECC ON: I + 8 + 3	-	-
Color Sensor	ECC OFF: I + 4	-	-
	ECC ON: I + 8 + 4	-	-
Sync	ECC OFF: I + 5	-	-
	ECC ON: I + 8 + 5	-	-

I = Highest channel number of selected mode

² Not available in DMX Effect Mode

DMX Value Allocation

Parameter	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
		Start	End	Start	End	Start	End	Start	End
Any	Neutral	0	19	0%	7%	0	4883	0%	7%
	- 1.000 → 0.000 (Neutral)	20	127	8%	50%	4884	32767	8%	50%
	Neutral	128	147	51%	57%	32768	37779	51%	57%
	0.000 (Neutral) → + 1.000	148	255	58%	100%	37780	65535	58%	100%



Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 1: 8 Bit
Mode 2: 16 Bit

Fixed Channels

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03/04		Color Temperature CCT	2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
03	05/06		Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
				Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
				-99 % → -1 %	21	119	9%	47%	9831	30145	16%	46%
				Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
				1 % → 99 %	146	244	58%	96%	39977	60292	62%	92%
04	07		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
05	08		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
06	09		Reserved	-	0	255	0%	100%	-	-	-	-

Variable Channels

Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
07	10	11	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
08	12	13	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
09	14	15	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
10	16	17	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
11	18	19	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
12	20	21	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
13	22	23	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
14	24	25	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
ECC	ECC		Fan Control <i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-
OFF	OFF			Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-
07	10			Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-
				High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-
ECC	ECC			Reserved	154	201	61%	78%	-	-	-	-
ON	ON			Fan at Full Speed	202	249	79%	98%	-	-	-	-
15	26		Fan Off	250	255	99%	100%	-	-	-	-	
ECC	ECC		Favorites User Defined Favorites	No Effect	0	9	1*	-	-	-	-	-
OFF	OFF			Favorite 01	10	-	-	-	-	-	-	-
08	11			Favorite 02	11	-	-	-	-	-	-	-
				Favorite 03	12	-	-	-	-	-	-	-
ECC	ECC			Favorite 04	13	-	-	-	-	-	-	-
ON	ON			Favorite 05	14	-	-	-	-	-	-	-
16	27			Favorite 06	15	-	-	-	-	-	-	-
				-	-	-	-	-	-	-
		Favorite 246	255	-	-	-	-	-	-	-		
ECC	ECC		Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-
OFF	OFF			1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-
09	12											
ECC	ECC		Color Sensor <i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Off	0	19	0%	7%	-	-	-	-
OFF	OFF			Continuous	20	127	8%	50%	-	-	-	-
10	13			Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC	ECC											
ON	ON											
18	29											
ECC	ECC		Sync <i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-
OFF	OFF			Sync Mode OFF	20	39	8%	15%	-	-	-	-
11	14			Sync Mode ON	40	59	16%	23%	-	-	-	-
				Reserved	60	255	24%	100%	-	-	-	-
ECC	ECC			(No Effect / Reverts to internal setting)								
ON	ON											
19	30											

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)



Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 3: 8 Bit
Mode 4: 16 Bit

Fixed Channels

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03/04		Hue	0 ° → 360°	0	255	0%	100%	0	65535	0%	100%
03	05/06		Saturation	0 → Full Saturation	0	255	0%	100%	0	65535	0%	100%
04	07		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
05	08		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
06	09		Reserved	-	0	255	0%	100%	-	-	-	-

Variable Channels

Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
07	10	11	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
08	12	13	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
09	14	15	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
10	16	17	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
11	18	19	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
12	20	21	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
13	22	23	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
14	24	25	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
ECC	ECC		Fan Control <i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-
OFF	OFF			Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-
07	10			Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-
				High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-
ECC	ECC			Reserved	154	201	61%	78%	-	-	-	-
ON	ON			Fan at Full Speed	202	249	79%	98%	-	-	-	-
15	26		Fan Off	250	255	99%	100%	-	-	-	-	
ECC	ECC		Favorites User Defined Favorites	No Effect	0	9	1*	-	-	-	-	-
OFF	OFF			Favorite 01	10	-	-	-	-	-	-	-
08	11			Favorite 02	11	-	-	-	-	-	-	-
				Favorite 03	12	-	-	-	-	-	-	-
ECC	ECC			Favorite 04	13	-	-	-	-	-	-	-
ON	ON			Favorite 05	14	-	-	-	-	-	-	-
16	27			Favorite 06	15	-	-	-	-	-	-	-
				-	-	-	-	-	-	-
		Favorite 246	255	-	-	-	-	-	-	-		
ECC	ECC		Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-
OFF	OFF			1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-
09	12											
ECC	ECC		Color Sensor <i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Off	0	19	0%	7%	-	-	-	-
OFF	OFF			Continuous	20	127	8%	50%	-	-	-	-
10	13			Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC	ECC	18	29									
ECC	ECC		Sync <i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-
OFF	OFF			Sync Mode OFF	20	39	8%	15%	-	-	-	-
11	14			Sync Mode ON	40	59	16%	23%	-	-	-	-
ECC	ECC			Reserved (No Effect / Reverts to internal setting)	60	255	24%	100%	-	-	-	-
ON	ON	19	30									

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)



Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 5: 8 Bit
Mode 6: 16 Bit

Fixed Channels

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03/04		X Coordinate	0.0 - 0.8	0	255	0%	100%	0	65535	0%	100%
03	05/06		Y Coordinate	0.0 - 0.8	0	255	0%	100%	0	65535	0%	100%
04	07		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
05	08		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
06	09		Reserved	-	0	255	0%	100%	-	-	-	-

Variable Channels

Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
07	10	11	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
08	12	13	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
09	14	15	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
10	16	17	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
11	18	19	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
12	20	21	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
13	22	23	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
14	24	25	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
ECC	ECC		Fan Control <i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-
OFF	OFF			Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-
07	10			Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-
				High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-
ECC	ECC			Reserved	154	201	61%	78%	-	-	-	-
ON	ON			Fan at Full Speed	202	249	79%	98%	-	-	-	-
15	26		Fan Off	250	255	99%	100%	-	-	-	-	
ECC	ECC		Favorites User Defined Favorites	No Effect	0	9	1*	-	-	-	-	-
OFF	OFF			Favorite 01	10	-	-	-	-	-	-	-
08	11			Favorite 02	11	-	-	-	-	-	-	-
				Favorite 03	12	-	-	-	-	-	-	-
ECC	ECC			Favorite 04	13	-	-	-	-	-	-	-
ON	ON			Favorite 05	14	-	-	-	-	-	-	-
16	27			Favorite 06	15	-	-	-	-	-	-	-
				-	-	-	-	-	-	-
		Favorite 246	255	-	-	-	-	-	-	-		
ECC	ECC		Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-
OFF	OFF			1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-
09	12											
ECC	ECC		Color Sensor <i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Off	0	19	0%	7%	-	-	-	-
OFF	OFF			Continuous	20	127	8%	50%	-	-	-	-
10	13			Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC	ECC		Sync <i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-
OFF	OFF			Sync Mode OFF	20	39	8%	15%	-	-	-	-
11	14			Sync Mode ON	40	59	16%	23%	-	-	-	-
ECC	ECC			Reserved (No Effect / Reverts to internal setting)	60	255	24%	100%	-	-	-	-
ON	ON											
19	30											

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)



Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 7: 8 Bit
Mode 8: 16 Bit

Fixed Channels

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03/04	GEL	Gel, CCT Selection	2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
03	05	GEL	Gel, Color Matching Selection	Best Color <i>Note: Color Quality Optimized</i>	0	84	0%	33%	-	-	-	-
				Brightest <i>Note: Color Brightness Optimized</i>	85	170	34%	66%	-	-	-	-
				No Color Gel	171	255	67%	100%	-	-	-	-
04	06	GEL	Gel, Brand	Choose Category on Channel 5, Gel on Channel 6								
				Rosco	0	127	0%	50%	-	-	-	-
				LEE Filters	128	255	51%	100%	-	-	-	-
05	07	GEL	Gel, Category (Brand Dependent)	Choose Gel Manufacturer on Channel 4								
				Category 1 Rosco: Color Correction LEE: Color Correction	0	50	0%	20%	-	-	-	-
				Category 2 Rosco: CalColor LEE: Color Filters	51	101	21%	39%	-	-	-	-
				Category 3 Rosco: Storaro Selection LEE: 600 Series	102	152	40%	60%	-	-	-	-
				Category 4 Rosco: Roscolux LEE: Cosmetic Filters	153	203	61%	80%	-	-	-	-
				Category 5 LEE: 700 Series	204	255	81%	100%	-	-	-	-
06	08	GEL	Gel	See "Gels" Table	0	255	0%	100%	-	-	-	-
07	09		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
08	10		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
09	11		Reserved	-	0	255	0%	100%	-	-	-	-

Category 1 | Rosco: Color Correction

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Full CTB	3202	0	-	256	-
		3/4 CTB	3203	1	-	512	-
		1/2 CTB	3204	2	-	768	-
		1/3 CTB	3206	3	-	1024	-
		1/4 CTB	3208	4	-	1280	-
		1/8 CTB	3216	5	-	1536	-
		Double CTB	3220	6	-	1792	-
		Full CTO	3407	7	-	2048	-
		3/4 CTO	3411	8	-	2304	-
		1/2 CTO	3408	9	-	2560	-
		1/4 CTO	3409	10	-	2816	-
		1/8 CTO	3410	11	-	3072	-
		Double CTO	3420	12	-	3328	-
		Full CTS	3441	13	-	3584	-
		1/2 CTS	3442	14	-	3840	-
		1/4 CTS	3443	15	-	4096	-
		1/8 CTS	3444	16	-	4352	-
		Full Plusgreen	3304	17	-	4608	-
		1/2 Plusgreen	3315	18	-	4864	-
		1/4 Plusgreen	3316	19	-	5120	-
		1/8 Plusgreen	3317	20	-	5376	-
		Full Minusgreen	3308	21	-	5632	-
		3/4 Minusgreen	3309	22	-	5888	-
		1/2 Minusgreen	3313	23	-	6144	-
		1/4 Minusgreen	3314	24	-	6400	-
		1/8 Minusgreen	3318	25	-	6656	-
		Fluorofilter	3310	26	-	6912	-
		Industrial Vapor	3150	27	-	7168	-
		Urban Vapor	3152	28	-	7424	-
		Tough Y-1	3107	29	-	7680	-
		Tough MT 54	3134	30	-	7936	-
		Tough MTY	3106	31	-	8192	-
	Tough MT2	3102	32	-	8448	-	
	Reserved for Future Use	-	-	33 - 255	-	8449 - 65535	-

Category 2 | Rosco: CalColor

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		15 Blue	4215	0	-	256	-
		30 Blue	4230	1	-	512	-
		60 Blue	4260	2	-	768	-
		90 Blue	4290	3	-	1024	-
		7 Cyan	4307	4	-	1280	-
		15 Cyan	4315	5	-	1536	-
		30 Cyan	4330	6	-	1792	-
		60 Cyan	4360	7	-	2048	-
		90 Cyan	4390	8	-	2304	-
		15 Green	4415	9	-	2560	-
		30 Green	4430	10	-	2816	-
		60 Green	4460	11	-	3072	-
		90 Green	4490	12	-	3328	-
		15 Yellow	4515	13	-	3584	-
		30 Yellow	4530	14	-	3840	-
		60 Yellow	4560	15	-	4096	-
		90 Yellow	4590	16	-	4352	-
		15 Red	4615	17	-	4608	-
		30 Red	4630	18	-	4864	-
		60 Red	4660	19	-	5120	-
		90 Red	4690	20	-	5376	-
		15 Magenta	4715	21	-	5632	-
		30 Magenta	4730	22	-	5888	-
		60 Magenta	4760	23	-	6144	-
		90 Magenta	4790	24	-	6400	-
		15 Pink	4815	25	-	6656	-
		30 Pink	4830	26	-	6912	-
		60 Pink	4860	27	-	7168	-
	90 Pink	4890	28	-	7424	-	
	15 Lavender	4915	29	-	7680	-	
	30 Lavender	4930	30	-	7936	-	
	60 Lavender	4960	31	-	8192	-	
	90 Lavender	4990	32	-	8448	-	
	Reserved for Future Use	-	-	33 - 255	-	8449 - 65535	-

Category 3 | Rosco: Storaro Selection

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		VS Red	2001	0	-	256	-
		VS Orange	2002	1	-	512	-
		VS Yellow	2003	2	-	768	-
		VS Green	2004	3	-	1024	-
		VS Cyan	2005	4	-	1280	-
		VS Azure	2006	5	-	1536	-
		VS Blue	2007	6	-	1792	-
		VS Indigo	2008	7	-	2048	-
		VS Violet	2009	8	-	2304	-
		VS Magenta	2010	9	-	2560	-
		Reserved for Future Use	-	-	10 - 255	-	2561 - 65535

Category 4 | Rosco: Roscolux

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Light Bastard Amber	1	0	-	256	-
		Bastard Amber	2	1	-	512	-
		Pale Bastard Amber	302	2	-	768	-
		Dark Bastard Amber	3	3	-	1024	-
		Warm Peach	303	4	-	1280	-
		Medium Bastard Amber	4	5	-	1536	-
		Pale Apricot	304	6	-	1792	-
		Rose Tint	5	7	-	2048	-
		Rose Gold	305	8	-	2304	-
		No Color Straw	6	9	-	2560	-
		Pale Yellow	7	10	-	2816	-
		Pale Gold	8	11	-	3072	-
		Pale Amber Gold	9	12	-	3328	-
		Medium Yellow	10	13	-	3584	-
		Daffodil	310	14	-	3840	-
		Light Straw	11	15	-	4096	-
		Straw	12	16	-	4352	-
		Canary	312	17	-	4608	-
		Straw Tint	13	18	-	4864	-
		Light Relief Yellow	313	19	-	5120	-
		Medium Straw	14	20	-	5376	-
		Deep Straw	15	21	-	5632	-
		Light Amber	16	22	-	5888	-
		Gallo Gold	316	23	-	6144	-
		Light Flame	17	24	-	6400	-
		Apricot	317	25	-	6656	-
		Flame	18	26	-	6912	-
		Mayan Sun	318	27	-	7168	-
		Fire	19	28	-	7424	-
		Medium Amber	20	29	-	7680	-
		Golden Amber	21	30	-	7936	-
		Soft Golden Amber	321	31	-	8192	-
		Deep Amber	22	32	-	8448	-
		Orange	23	33	-	8704	-
	Henna Sky	325	34	-	8960	-	
	Scarlet	24	35	-	9216	-	
	Gypsy Red	324	36	-	9472	-	
	Orange Red	25	37	-	9728	-	
	Light Red	26	38	-	9984	-	
	Medium Red	27	39	-	10240	-	
	Light Salmon Pink	30	40	-	10496	-	
	Salmon Pink	31	41	-	10752	-	
	Shell Pink	331	42	-	11008	-	
	Medium Salmon Pink	32	43	-	11264	-	
	Cherry Rose	332	44	-	11520	-	
	No Color Pink	33	45	-	11776	-	
	Blush Pink	333	46	-	12032	-	
	Flesh Pink	34	47	-	12288	-	
	Light Pink	35	48	-	12544	-	
	Medium Pink	36	49	-	12800	-	
	Billinton Pink	336	50	-	13056	-	
	Pale Rose Pink	37	51	-	13312	-	
	True Pink	337	52	-	13568	-	
	Light Rose	38	53	-	13824	-	
	Skelton Exotic Sangria	39	54	-	14080	-	
	Broadway Pink	339	55	-	14336	-	
	Light Salmon	40	56	-	14592	-	
	Salmon	41	57	-	14848	-	
	Deep Salmon	42	58	-	15104	-	
	Rose Pink	342	59	-	15360	-	

Category 4 | Rosco: Roscolux (continued)

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Deep Pink	43	60	-	15616	-
		Neon Pink	343	61	-	15872	-
		Middle Rose	44	62	-	16128	-
		Follies Pink	344	63	-	16384	-
		Rose	45	64	-	16640	-
		Magenta	46	65	-	16896	-
		Tropical Magenta	346	66	-	17152	-
		Light Rose Purple	47	67	-	17408	-
		Belladonna Rose	347	68	-	17664	-
		Rose Purple	48	69	-	17920	-
		Purple Jazz	348	70	-	18176	-
		Medium Purple	49	71	-	18432	-
		Fisher Fuchsia	349	72	-	18688	-
		Mauve	50	73	-	18944	-
		Surprise Pink	51	74	-	19200	-
		Lavender Mist	351	75	-	19456	-
		Light Lavender	52	76	-	19712	-
		Pale Lavender	53	77	-	19968	-
		Lilly Lavender	353	78	-	20224	-
		Special Lavender	54	79	-	20480	-
		Lilac	55	80	-	20736	-
		Pale Violet	355	81	-	20992	-
		Gypsy Lavender	56	82	-	21248	-
		Middle Lavender	356	83	-	21504	-
		Lavender	57	84	-	21760	-
		Royal Lavender	357	85	-	22016	-
		Deep Lavender	58	86	-	22272	-
		Rose Indigo	358	87	-	22528	-
		Indigo	59	88	-	22784	-
		Medium Violet	359	89	-	23040	-
		No Color Blue	60	90	-	23296	-
		Clearwater	360	91	-	23552	-
		Mist Blue	61	92	-	23808	-
		Hemsley Blue	361	93	-	24064	-
		Booster Blue	62	94	-	24320	-
		Tipton Blue	362	95	-	24576	-
		Pale Blue	63	96	-	24832	-
		Aquamarine	363	97	-	25088	-
		Light Steel Blue	64	98	-	25344	-
		Blue Bell	364	99	-	25600	-
		Daylight Blue	65	100	-	25856	-
		Tharon Delft Blue	365	101	-	26112	-
		Cool Blue	66	102	-	26368	-
		Jordan Blue	366	103	-	26624	-
		Light Sky Blue	67	104	-	26880	-
		Slate Blue	367	105	-	27136	-
	Parry Sky Blue	68	106	-	27392	-	
	Winkler Blue	368	107	-	27648	-	
	Brilliant Blue	69	108	-	27904	-	
	Tahitian Blue	369	109	-	28160	-	
	Nile Blue	70	110	-	28416	-	
	Italian Blue	370	111	-	28672	-	
	Sea Blue	71	112	-	28928	-	
	Azure Blue	72	113	-	29184	-	
	Peacock Blue	73	114	-	29440	-	
	Night Blue	74	115	-	29696	-	
	Sea Green	374	116	-	29952	-	
	Twilight Blue	75	117	-	30208	-	
	Cerulean Blue	375	118	-	30464	-	
	Light Green Blue	76	119	-	30720	-	

Category 4 | Rosco: Roscolux (continued)

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Bermuda Blue	376	120	-	30976	-
		Green Blue	77	121	-	31232	-
		Iris Purple	377	122	-	31488	-
		Trudy Blue	78	123	-	31744	-
		Alice Blue	378	124	-	32000	-
		Bright Blue	79	125	-	32256	-
		Primary Blue	80	126	-	32512	-
		Urban Blue	81	127	-	32768	-
		Baldassari Blue	381	128	-	33024	-
		Surprise Blue	82	129	-	33280	-
		Congo Blue	382	130	-	33536	-
		Medium Blue	83	131	-	33792	-
		Sapphire Blue	383	132	-	34048	-
		Zephyr Blue	84	133	-	34304	-
		Midnight Blue	384	134	-	34560	-
		Deep Blue	85	135	-	34816	-
		Royal Blue	385	136	-	35072	-
		Pea Green	86	137	-	35328	-
		Leaf Green	386	138	-	35584	-
		Pale Yellow Green	87	139	-	35840	-
		Light Green	88	140	-	36096	-
		Gaslight Green	388	141	-	36352	-
		Moss Green	89	142	-	36608	-
		Chroma Green	389	143	-	36864	-
		Primary Green	91	144	-	37120	-
		Pacific Green	392	145	-	37376	-
		Turquoise	92	146	-	37632	-
		Blue Green	93	147	-	37888	-
		Emerald Green	393	148	-	38144	-
		Teal Green	395	149	-	38400	-
	Lime	96	150	-	38656	-	
	Pale Grey	397	151	-	38912	-	
	Neutral Grey	398	152	-	39168	-	
	Chocolate	99	153	-	39424	-	
	Reserved for Future Use	-	154 - 255	-	39425 - 65535	-	

Category 1 | Lee: Color Correction

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Double CTB	200	0	-	256	-
		Full CTB	201	1	-	512	-
		3/4 CTB	281	2	-	768	-
		1/2 CTB	202	3	-	1024	-
		1/4 CTB	203	4	-	1280	-
		1/8 CTB	218	5	-	1536	-
		Double CTO	287	6	-	1792	-
		Full CTO	204	7	-	2048	-
		3/4 CTO	285	8	-	2304	-
		1/2 CTO	205	9	-	2560	-
		1/4 CTO	206	10	-	2816	-
		1/8 CTO	223	11	-	3072	-
		1 1/2 CTB	283	12	-	3328	-
		1 1/2 CTO	286	13	-	3584	-
		Full CTS	441	14	-	3840	-
		1/2 CTS	442	15	-	4096	-
		1/4 CTS	443	16	-	4352	-
		1/8 CTS	444	17	-	4608	-
		Full CTO + .3 ND	207	18	-	4864	-
		Full CTO + .6 ND	208	19	-	5120	-
		L.C.T. Yellow (Y1)	212	20	-	5376	-
		White Flame Green	213	21	-	5632	-
		LEE Fluorescent Green	219	22	-	5888	-
		Super Correction L.C.T. Yellow	230	23	-	6144	-
		Super Correction W.F. Green	232	24	-	6400	-
		H.M.I. (to Tungsten)	236	25	-	6656	-
		C.I.D. (to Tungsten)	237	26	-	6912	-
		C.S.I. (to Tungsten)	238	27	-	7168	-
		LEE Fluorescent 5700 Kelvin	241	28	-	7424	-
		LEE Fluorescent 4300 Kelvin	242	29	-	7680	-
		LEE Fluorescent 3600 Kelvin	243	30	-	7936	-
		LEE Plus Green	244	31	-	8192	-
		1/2 Plus Green	245	32	-	8448	-
	1/4 Plus Green	246	33	-	8704	-	
	1/8 Plus Green	278	34	-	8960	-	
	Lee Minus Green	247	35	-	9216	-	
	1/2 Minus Green	248	36	-	9472	-	
	1/4 Minus Green	249	37	-	9728	-	
	1/8 Minus Green	279	38	-	9984	-	
	Reserved for Future Use	-	39 - 255	-	9985 - 65535	-	

Category 2 | Lee: Color Filters

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Rose Pink	002	0	-	256	-
		Lavender Tint	003	1	-	512	-
		Medium Bastard Amber	004	2	-	768	-
		Pale Yellow	007	3	-	1024	-
		Dark Salmon	008	4	-	1280	-
		Pale Amber Gold	009	5	-	1536	-
		Medium Yellow	010	6	-	1792	-
		Straw Tint	013	7	-	2048	-
		Deep Straw	015	8	-	2304	-
		Surprise Peach	017	9	-	2560	-
		Fire	019	10	-	2816	-
		Medium Amber	020	11	-	3072	-
		Gold Amber	021	12	-	3328	-
		Dark Amber	022	13	-	3584	-
		Scarlet	024	14	-	3840	-
		Sunset Red	025	15	-	4096	-
		Bright Red	026	16	-	4352	-
		Medium Red	027	17	-	4608	-
		PLASA Red	029	18	-	4864	-
		Light Pink	035	19	-	5120	-
		Medium Pink	036	20	-	5376	-
		Dark Magenta	046	21	-	5632	-
		Rose Purple	048	22	-	5888	-
		Medium Purple	049	23	-	6144	-
		Light Lavender	052	24	-	6400	-
		Paler Lavender	053	25	-	6656	-
		Lavender	058	26	-	6912	-
		Mist Blue	061	27	-	7168	-
		Pale Blue	063	28	-	7424	-
		Sky Blue	068	29	-	7680	-
		Tokyo Blue	071	30	-	7936	-
		Evening Blue	075	31	-	8192	-
		Just Blue	079	32	-	8448	-
		Deeper Blue	085	33	-	8704	-
		Lime Green	088	34	-	8960	-
		Moss Green	089	35	-	9216	-
		Dark Yellow Green	090	36	-	9472	-
		Spring Yellow	100	37	-	9728	-
		Yellow	101	38	-	9984	-
		Light Amber	102	39	-	10240	-
		Straw	103	40	-	10496	-
		Deep Amber	104	41	-	10752	-
		Orange	105	42	-	11008	-
		Primary Red	106	43	-	11264	-
		Light Rose	107	44	-	11520	-
		English Rose	108	45	-	11776	-
		Light Salmon	109	46	-	12032	-
		Middle Rose	110	47	-	12288	-
		Dark Pink	111	48	-	12544	-
		Magenta	113	49	-	12800	-
		Peacock Blue	115	50	-	13056	-
		Medium Blue-Green	116	51	-	13312	-
		Steel Blue	117	52	-	13568	-
		Light Blue	118	53	-	13824	-
		Dark Blue	119	54	-	14080	-
		Deep Blue	120	55	-	14336	-
		LEE Green	121	56	-	14592	-
		Fern Green	122	57	-	14848	-
		Dark Green	124	58	-	15104	-
	Mauve	126	59	-	15360	-	

Category 2 | Lee: Color Filters (continued)

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Smokey Pink	127	60	-	15616	-
		Bright Pink	128	61	-	15872	-
		Marine Blue	131	62	-	16128	-
		Medium Blue	132	63	-	16384	-
		Golden Amber	134	64	-	16640	-
		Deep Golden Amber	135	65	-	16896	-
		Pale Lavender	136	66	-	17152	-
		Special Lavender	137	67	-	17408	-
		Pale Green	138	68	-	17664	-
		Primary Green	139	69	-	17920	-
		Summer Blue	140	70	-	18176	-
		Bright Blue	141	71	-	18432	-
		Pale Violet	142	72	-	18688	-
		Pale Navy Blue	143	73	-	18944	-
		No Color Blue	144	74	-	19200	-
		Apricot	147	75	-	19456	-
		Bright Rose	148	76	-	19712	-
		Gold Tint	151	77	-	19968	-
		Pale Gold	152	78	-	20224	-
		Pale Salmon	153	79	-	20480	-
		Pale Rose	154	80	-	20736	-
		Chocolate	156	81	-	20992	-
		Pink	157	82	-	21248	-
		Deep Orange	158	83	-	21504	-
		No Color Straw	159	84	-	21760	-
		Slate Blue	161	85	-	22016	-
		Bastard Amber	162	86	-	22272	-
		Flame Red	164	87	-	22528	-
		Daylight Blue	165	88	-	22784	-
		Lilac Tint	169	89	-	23040	-
		Deep Lavender	170	90	-	23296	-
		Lagoon Blue	172	91	-	23552	-
		Dark Steel Blue	174	92	-	23808	-
		Loving Amber	176	93	-	24064	-
		Chrome Orange	179	94	-	24320	-
		Dark Lavender	180	95	-	24576	-
		Congo Blue	181	96	-	24832	-
		Light Red	182	97	-	25088	-
		Moonlight Blue	183	98	-	25344	-
		Flesh Pink	192	99	-	25600	-
		Surprise Pink	194	100	-	25856	-
		Zenith Blue	195	101	-	26112	-
		True Blue	196	102	-	26368	-
		Alice Blue	197	103	-	26624	-
		Palace Blue	198	104	-	26880	-
		Regal Blue	199	105	-	27136	-
		Soft Green	322	106	-	27392	-
		Jade	323	107	-	27648	-
	Forest Green	327	108	-	27904	-	
	Follies Pink	328	109	-	28160	-	
	Special Rose Pink	332	110	-	28416	-	
	Special Med Lavender	343	111	-	28672	-	
	Fuchsia Pink	345	112	-	28928	-	
	Glacier Blue	352	113	-	29184	-	
	Lighter Blue	353	114	-	29440	-	
	Special Steel Blue	354	115	-	29696	-	
	Special Medium Blue	363	116	-	29952	-	
	Cornflower	366	117	-	30208	-	
	Double New Colour Blue	500	118	-	30464	-	
	New Colour Robertson	501	119	-	30720	-	

Category 2 | Lee: Color Filters (continued)

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Half New Colour Blue	502	120	-	30976	-
		Quarter New Colour Blue	503	121	-	31232	-
		Waterfront Green	504	122	-	31488	-
		Sally Green	505	123	-	31744	-
		Marlene	506	124	-	32000	-
		Madge	507	125	-	32256	-
		Midnight Maya	508	126	-	32512	-
		Bacon Brown	511	127	-	32768	-
		Amber Delight	512	128	-	33024	-
		Ice & a Slice	513	129	-	33280	-
		Double G & T	514	130	-	33536	-
		Argent Blue	525	131	-	33792	-
		ALD Gold	550	132	-	34048	-
		Reserved for Future Use	-	133 - 255	-	34049 - 65535	-

Category 3 | Lee: 600 Series

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Arctic White	600	0	-	256	-
		Silver	601	1	-	512	-
		Platinum	602	2	-	768	-
		Moonlight White	603	3	-	1024	-
		Full CT 85	604	4	-	1280	-
		Half Mustard Yellow	642	5	-	1536	-
		Quarter Mustard Yellow	643	6	-	1792	-
		Industry Sodium	650	7	-	2048	-
		HI Sodium	651	8	-	2304	-
		Urban Sodium	652	9	-	2560	-
		LO Sodium	653	10	-	2816	-
		Reserved for Future Use	-	11 - 255	-	2817 - 65535	-

Category 4 | Lee: Cosmetic Filters

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Cosmetic Peach	184	0	-	256	-
		Cosmetic Silver Rose	186	1	-	512	-
		Cosmetic Rouge	187	2	-	768	-
		Cosmetic Highlight	188	3	-	1024	-
		Cosmetic Silver Moss	189	4	-	1280	-
		Cosmetic Aqua Blue	191	5	-	1536	-
		Lily Frost	705	6	-	1792	-
		Shanklin Frost	717	7	-	2048	-
		Half Shanklin Frost	718	8	-	2304	-
		Durham Daylight Frost	720	9	-	2560	-
		Hampshire Rose	749	10	-	2816	-
		Durham Frost	750	11	-	3072	-
		Soft Amber Key 1	774	12	-	3328	-
		Soft Amber Key 2	775	13	-	3584	-
		Moroccan Frost	791	14	-	3840	-
		Blue Diffusion	217	15	-	4096	-
		Blue Frost	221	16	-	4352	-
		Daylight Blue Frost	224	17	-	4608	-
		Reserved for Future Use	-	18 - 255	-	4609 - 65535	-

Category 5 | Lee: 700 Series

*16 Bit Ultimate Mode only

DMX Channel		Gel Name	Gel Number	Value 8 Bit	% 8 Bit	Value 16 Bit*	% 16 Bit
8 Bit	16 Bit						
Dependent on Mode		Perfect Lavender	700	0	-	256	-
		Provence	701	1	-	512	-
		Special Pale Lavender	702	2	-	768	-
		Cold Lavender	703	3	-	1024	-
		Lily	704	4	-	1280	-
		King Fals Lavender	706	5	-	1536	-
		Cool Lavender	708	6	-	1792	-
		Electric Lilac	709	7	-	2048	-
		Spir Special Blue	710	8	-	2304	-
		Cold Blue	711	9	-	2560	-
		Bedford Blue	712	10	-	2816	-
		J Winter Blue	713	11	-	3072	-
		Elysian Blue	714	12	-	3328	-
		Cabana Blue	715	13	-	3584	-
		Mikkel Blue	716	14	-	3840	-
		Colour Wash Blue	719	15	-	4096	-
		Berry Blue	721	16	-	4352	-
		Bray Blue	722	17	-	4608	-
		Virgin Blue	723	18	-	4864	-
		Ocean Blue	724	19	-	5120	-
		Old Steel Blue	725	20	-	5376	-
		QFD Blue	727	21	-	5632	-
		Steel Green	728	22	-	5888	-
		Scuba Blue	729	23	-	6144	-
		Liberty Green	730	24	-	6400	-
		Dirty Ice	731	25	-	6656	-
		Damp Squib	733	26	-	6912	-
		Velvet Green	735	27	-	7168	-
		Twickenham Green	736	28	-	7424	-
		JAS Green	738	29	-	7680	-
		Aurora Borealis Green	740	30	-	7936	-
		Mustard Yellow	741	31	-	8192	-
		Bram Brown	742	32	-	8448	-
		Dirty White	744	33	-	8704	-
		Brown	746	34	-	8960	-
		Easy White	747	35	-	9216	-
		Seedy Pink	748	36	-	9472	-
		Wheat	763	37	-	9728	-
		Sun Colour Straw	764	38	-	9984	-
		LEE Yellow	765	39	-	10240	-
		Oklahoma Yellow	767	40	-	10496	-
		Egg Yolk Yellow	768	41	-	10752	-
		Burnt Yellow	770	42	-	11008	-
		Cardbox Amber	773	43	-	11264	-
		Nectarine	776	44	-	11520	-
		Rust	777	45	-	11776	-
		Millenium Gold	778	46	-	12032	-
		Bastard Pink	779	47	-	12288	-
		AS Golden Amber	780	48	-	12544	-
		Terry Red	781	49	-	12800	-
	Marius Red	787	50	-	13056	-	
	Blood Red	789	51	-	13312	-	
	Moroccan Pink	790	52	-	13568	-	
	Vanity Fair	793	53	-	13824	-	
	Pretty n'Pink	794	54	-	14080	-	
	Magical Magenta	795	55	-	14336	-	
	Deep Purple	797	56	-	14592	-	
	Chrysalis Pink	798	57	-	14848	-	
	Special KH Lavender	799	58	-	15104	-	
	Reserved for Future Use	-	59 - 255	-	15105 - 65535	-	

Variable Channels




Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
10	12	13	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
11	14	15	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
12	16	17	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
13	18	19	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
14	20	21	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
15	22	23	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
16	24	25	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
17	26	27	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel			Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit			
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End		
ECC OFF 10	ECC OFF 12		Fan Control <i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-		
				Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-		
				Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-		
				High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-		
				Reserved	154	201	61%	78%	-	-	-	-		
ECC ON 18	ECC ON 28					Fan at Full Speed	202	249	79%	98%	-	-	-	-
						Fan Off	250	255	99%	100%	-	-	-	-
ECC OFF 11	ECC OFF 13	★	Favorites User Defined Favorites	No Effect	0	9	1*	-	-	-	-	-		
				Favorite 01	10	-	-	-	-	-	-	-	-	
				Favorite 02	11	-	-	-	-	-	-	-	-	
				Favorite 03	12	-	-	-	-	-	-	-	-	
ECC ON 19	ECC ON 29					Favorite 04	13	-	-	-	-	-	-	
						Favorite 05	14	-	-	-	-	-	-	
						Favorite 06	15	-	-	-	-	-	-	
						-	-	-	-	-	-	
ECC OFF 12	ECC OFF 14	⚡	Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-		
				1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-		
ECC ON 20	ECC ON 30													
ECC OFF 13	ECC OFF 15		Color Sensor <i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Off	0	19	0%	7%	-	-	-	-		
				Continuous	20	127	8%	50%	-	-	-	-		
ECC ON 21	ECC ON 31					Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC OFF 14	ECC OFF 16		Sync <i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-		
				Sync Mode OFF	20	39	8%	15%	-	-	-	-		
				Sync Mode ON	40	59	16%	23%	-	-	-	-		
ECC ON 22	ECC ON 32					Reserved (No Effect / Reverts to internal setting)	60	255	24%	100%	-	-	-	-

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)



Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 9: 8 Bit
Mode 10: 16 Bit

Fixed Channels

DMX Channel			Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03		Category	Incandescent	0	50	0%	20%	-	-	-	-
				Fluorescent	51	101	21%	39%	-	-	-	-
				Discharge	102	152	40%	59%	-	-	-	-
				Other	153	203	60%	79%	-	-	-	-
				Reserved for Future Use	204	255	80%	100%	-	-	-	-
03	04		Source	See "Source" Table	0	255	0%	100%	-	-	-	-
04	05		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
05	06		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
06	07		Reserved	-	0	255	0%	100%	-	-	-	-

Incandescent

*Ultimate Mode only

DMX Channel		Category	Name	Value 8 Bit		% 8 Bit		Value 16 Bit*		% 16 Bit	
8 Bit	16 Bit			Start	End	Start	End	Start	End	Start	End
Dependent on Mode	Incandescent	Tungsten Bulb	0	2	-	-	0	767	-	-	
		Incandescent	3	5	-	-	768	1535	-	-	
		Halogen	6	8	-	-	1536	2303	-	-	
		Antique Bulb	9	11	-	-	2304	3071	-	-	
		Warm Antique Bulb	12	14	-	-	3072	3839	-	-	
		Christmas Light	15	17	-	-	3840	4607	-	-	
		Night Light	18	20	-	-	4608	5375	-	-	
		Infrared Heat Lamp	21	23	-	-	5376	6143	-	-	
		Grow Light	24	26	-	-	6144	6911	-	-	
		Reserved for Future Use	27	255	-	-	6912	65535	-	-	

Fluorescent

*Ultimate Mode only

DMX Channel		Category	Name	Value 8 Bit		% 8 Bit		Value 16 Bit*		% 16 Bit	
8 Bit	16 Bit			Start	End	Start	End	Start	End	Start	End
Dependent on Mode	Fluorescent	CFL Soft White	0	2	-	-	0	767	-	-	
		CFL Bright White	3	5	-	-	768	1535	-	-	
		CFL Cool White	6	8	-	-	1536	2303	-	-	
		CFL Daylight	9	11	-	-	2304	3071	-	-	
		Cool White 1	12	14	-	-	3072	3839	-	-	
		Cool White 2	15	17	-	-	3840	4607	-	-	
		Cool White 3	18	20	-	-	4608	5375	-	-	
		Warm White	21	23	-	-	5376	6143	-	-	
		CFL Blacklight	24	26	-	-	6144	6911	-	-	
		Reserved for Future Use	27	255	-	-	6912	65535	-	-	

Discharge

*Ultimate Mode only

DMX Channel		Category	Name	Value 8 Bit		% 8 Bit		Value 16 Bit*		% 16 Bit	
8 Bit	16 Bit			Start	End	Start	End	Start	End	Start	End
Dependent on Mode	Discharge	HMI	0	2	-	-	0	767	-	-	
		High Pressure Sodium	3	5	-	-	768	1535	-	-	
		Low Pressure Sodium	6	8	-	-	1536	2303	-	-	
		Mercury Vapor	9	11	-	-	2304	3071	-	-	
		Metal Halide	12	14	-	-	3072	3839	-	-	
		Ceramic	15	17	-	-	3840	4607	-	-	
		Carbon Arc	18	20	-	-	4608	5375	-	-	
		Xenon	21	23	-	-	5376	6143	-	-	
		Reserved for Future Use	24	255	-	-	6144	65535	-	-	

Other

*Ultimate Mode only

DMX Channel		Category	Name	Value 8 Bit		% 8 Bit		Value 16 Bit*		% 16 Bit	
8 Bit	16 Bit			Start	End	Start	End	Start	End	Start	End
Dependent on Mode	Other	Candle	0	2	-	-	0	767	-	-	
		Gas Fire	3	5	-	-	768	1535	-	-	
		Sun Direct	6	8	-	-	1536	2303	-	-	
		Sun Overcast	9	11	-	-	2304	3071	-	-	
		Sun Blue Hour	12	14	-	-	3072	3839	-	-	
		Mobile Phone	15	17	-	-	3840	4607	-	-	
		Computer Monitor	18	20	-	-	4608	5375	-	-	
		Electroluminescence	21	23	-	-	5376	6143	-	-	
		Blow Torch	24	26	-	-	6144	6911	-	-	
		Road Flare	27	29	-	-	6912	7679	-	-	
		Amber Caution	30	32	-	-	7680	8447	-	-	
		Green Traffic Light	33	35	-	-	8448	9215	-	-	
		Yellow Traffic Light	36	38	-	-	9216	9983	-	-	
		Red Traffic Light	39	41	-	-	9984	10751	-	-	
		Blue Glow Stick	42	44	-	-	10752	11519	-	-	
		Green Glow Stick	45	47	-	-	11520	12287	-	-	
		Red Glow Stick	48	50	-	-	12288	13055	-	-	
		Yellow Glow Stick	51	53	-	-	13056	13823	-	-	
		Pink Glow Stick	54	56	-	-	13824	14591	-	-	
Violet Glow Stick	57	59	-	-	14592	15359	-	-			
	Reserved for Future Use	60	255	-	-	15360	65535	-	-		

Variable Channels







Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
07	08	09	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
08	10	11	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
09	12	13	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
10	14	15	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
11	16	17	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
12	18	19	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
13	20	21	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
14	22	23	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel			Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit			
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End		
ECC	ECC		Fan Control	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-		
OFF	OFF		<i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>		Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-	
07	08				Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-	
					High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-	
ECC	ECC				Reserved	154	201	61%	78%	-	-	-	-	
ON	ON				Fan at Full Speed	202	249	79%	98%	-	-	-	-	
15	24				Fan Off	250	255	99%	100%	-	-	-	-	
ECC	ECC			Favorites	No Effect	0	9	1*	-	-	-	-	-	
OFF	OFF		User Defined Favorites		Favorite 01	10	-	-	-	-	-	-	-	
08	09				Favorite 02	11	-	-	-	-	-	-	-	
					Favorite 03	12	-	-	-	-	-	-	-	
ECC	ECC				Favorite 04	13	-	-	-	-	-	-	-	
ON	ON				Favorite 05	14	-	-	-	-	-	-	-	
16	25				Favorite 06	15	-	-	-	-	-	-	-	
					-	-	-	-	-	-	-	
					Favorite 246	255	-	-	-	-	-	-	-	
ECC	ECC			Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-	
OFF	OFF				1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-	
09	10													
ECC	ECC		Color Sensor	Off	0	19	0%	7%	-	-	-	-		
OFF	OFF			<i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Continuous	20	127	8%	50%	-	-	-	-	
10	11					Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC	ECC													
ON	ON													
18	27													
ECC	ECC		Sync	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-		
OFF	OFF			<i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Sync Mode OFF	20	39	8%	15%	-	-	-	-	
11	12					Sync Mode ON	40	59	16%	23%	-	-	-	-
						Reserved	60	255	24%	100%	-	-	-	-
ECC	ECC					(No Effect / Reverts to internal setting)								
ON	ON													
19	28													

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)



Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 11: 8 Bit
Mode 12: 16 Bit

Fixed Channels

DMX Channel			Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03		Effect Selection	No Effect	0	9	0%	4%	-	-	-	-
				Party Effect	10	19	5%	7%	-	-	-	-
				Candle	20	29	8%	11%	-	-	-	-
				Clouds Passing	30	39	12%	15%	-	-	-	-
				Club Lights	40	49	16%	19%	-	-	-	-
				Cop Car	50	59	20%	23%	-	-	-	-
				Fire	60	69	24%	27%	-	-	-	-
				Fireworks	70	79	28%	31%	-	-	-	-
				Light Strobe	80	89	32%	35%	-	-	-	-
				Lightning	90	99	36%	39%	-	-	-	-
				Paparazzi	100	109	40%	43%	-	-	-	-
				Pulsing	110	119	44%	47%	-	-	-	-
				Television	120	129	48%	51%	-	-	-	-
				Explosion	130	139	52%	55%	-	-	-	-
Fluorescent Flicker	140	149	56%	58%	-	-	-	-				
Welding	150	159	59%	62%	-	-	-	-				
			Reserved for Future Use		160	255	63%	100%	-	-	-	-
03	04/05		Effect Parameter 1	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
04	06/07		Effect Parameter 2	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
05	08/09		Effect Parameter 3	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
06	10/11		Effect Parameter 4	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
07	12/13		Effect Parameter 5	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
08	14/15		Effect Parameter 6	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
09	16/17		Effect Parameter 7	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
10	18/19		Effect Parameter 8	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
11	20		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
12	21		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
13	22		Reserved	-	0	255	0%	100%	-	-	-	-

Party Effect

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Saturation	CCT 2.000 K → 20.000 K	0	0	0%	0%	0	0	0%	0%
		0 → 100 % Saturation	1	255	1%	100%	1	65535	1%	100%
2	Sequence	Loop 60 s → 1 s	0	255	0%	100%	0	65535	0%	100%

Candle

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	CCT Range <i>Not continuous, set range for random generation</i>	1.400 K → 1.700 K	0	84	0%	32%	0	21759	0%	32%
		1.700 K → 2.000 K	85	170	33%	66%	21760	43775	33%	66%
		2.000 K → 2.300 K	171	255	67%	100%	43776	65535	67%	100%
2	Sequence	1 → 120 Changes / Min	0	255	0%	100%	0	65535	0%	100%

Clouds Passing

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Offset	Offset Number 0 - 50 (Every 5 DMX values is a new Offset)	0	255	0%	100%	0	65535	0%	100%
2	Sequence	2 x Slower → Default Speed	0	127	0%	49%	0	32767	0%	49%
		Default Speed → 2 x Faster	128	255	50%	100%	32768	65535	50%	100%
3	Trigger	If bumped to 255 (100%), the loop will start at zero (or depending on the offset value)	0	255	0%	100%	0	65535	0%	100%

Club Lights

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Color Variety	3 Colors	0	31	0%	12%	0	8191	0%	12%
		6 Colors	32	63	13%	24%	8192	16383	13%	24%
		9 Colors	64	95	25%	37%	16384	24575	25%	37%
		12 Colors	96	127	38%	49%	24576	32767	38%	49%
		15 Colors	128	159	50%	62%	32768	40959	50%	62%
		18 Colors	160	191	63%	74%	40960	49151	63%	74%
		21 Colors	192	223	75%	87%	49152	57343	75%	87%
2	Sequence	24 Colors	224	255	88%	100%	57344	65535	88%	100%
		1 → 120 Changes / Min	0	255	0%	100%	0	65535	0%	100%

Cop Car

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Color Combinations	Just Blue	0	27	0%	11%	0	7167	0%	11%
		Blue and Red	28	55	12%	21%	7168	14335	12%	21%
		Blue and White	56	83	22%	32%	14336	21503	22%	32%
		Blue, Red and White	84	111	33%	43%	21504	28671	33%	43%
		Blue and Amber	112	139	44%	54%	28672	35839	44%	54%
		Blue, Red and Amber	140	167	55%	65%	35840	43007	55%	65%
		Red and Amber	168	195	66%	76%	43008	50175	66%	76%
		Amber	196	223	77%	87%	50176	57343	77%	87%
2	Flash Pattern	Red	224	255	88%	100%	57344	65535	88%	100%
		Single Flash	0	31	0%	12%	0	8191	0%	12%
		Double Flash	32	63	13%	24%	8192	16383	13%	24%
		Quint All Flash	64	95	25%	37%	16384	24575	25%	37%
		Quint Flash	96	127	38%	49%	24576	32767	38%	49%
		Quad Flash	128	159	50%	62%	32768	40959	50%	62%
		Cycle All	160	191	63%	74%	40960	49151	63%	74%
Reserved for Future Use	192	255	75%	100%	49152	65535	75%	100%		

Fire

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	CCT Range <i>Not continuous, set range for random generation</i>	1.800 K → 2.200 K	0	84	0%	32%	0	21759	0%	32%
		2.200 K → 2.600 K	85	170	33%	66%	21760	43775	33%	66%
		2.600 K → 3.000 K	171	255	67%	100%	43776	65535	67%	100%
2	Sequence	1 → 180 Changes / Min	0	255	0%	100%	0	65535	0%	100%

Fireworks

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Color Combinations	Colors	0	63	0%	24%	0	16383	0%	24%
		White	64	127	25%	49%	16384	32767	25%	49%
		Colors and White	128	191	50%	74%	32768	49151	50%	74%
		Reserved for Future Use	192	255	75%	100%	49152	65535	75%	100%
2	Sequence	10 → 0,5 s Between Fireworks	0	255	0%	100%	0	65535	0%	100%

Light Strobe

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Sequence	1 → 25 Flashes / Second	0	255	0%	100%	0	65535	0%	100%
2	Color Temperature	CCT 2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
3	Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
		Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
		-99 % → -1%	21	119	9%	47%	9831	30145	16%	46%
		Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
		1% → 99 %	146	244	58%	96%	39977	60292	62%	92%
4	Cross Fade to Color	Full Plus Green	245	255	97%	100%	60293	65535	93%	100%
		White → Color	0	255	0%	100%	0	65535	0%	100%
5	Hue	0 → 360°	0	255	0%	100%	0	65535	0%	100%
6	Saturation	0 → 100 % Saturation	0	255	0%	100%	0	65535	0%	100%

Lightning

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Speed	2 → 14 Lightning Strikes Set	0	254	0%	99%	0	65534	0%	99%
		Random	255		100%		65535		100%	
2	Sequence	1 → 10 Flashes / Second	0	254	0%	99%	0	65534	0%	99%
		Random	255		100%		65535		100%	
3	Color Temperature	CCT 2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
4	Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
		Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
		-99 % → -1%	21	119	9%	47%	9831	30145	16%	46%
		Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
		1% → 99 %	146	244	58%	96%	39977	60292	62%	92%
	Full Plus Green	245	255	97%	100%	60293	65535	93%	100%	
5	Cross Fade to Color	White → Color	0	255	0%	100%	0	65535	0%	100%
6	Hue	0 → 360°	0	255	0%	100%	0	65535	0%	100%
7	Saturation	0 → 100 % Saturation	0	255	0%	100%	0	65535	0%	100%
8	Trigger	If bumped to 255 (100%), the loop will start at zero (or depending on the offset value)	0	255	0%	100%	0	65535	0%	100%

Paparazzi

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Speed	6 → 120 Flashes / Min	0	255	0%	100%	0	65535	0%	100%
2	Flash Type	Flash Bulb	0	127	0%	49%	0	32767	0%	49%
		Modern Flash	128	255	50%	100%	32768	65535	50%	100%
3	Color Temperature	CCT 2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
4	Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
		Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
		-99 % → -1%	21	119	9%	47%	9831	30145	16%	46%
		Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
		1% → 99 %	146	244	58%	96%	39977	60292	62%	92%
	Full Plus Green	245	255	97%	100%	60293	65535	93%	100%	
5	Cross Fade to Color	White → Color	0	255	0%	100%	0	65535	0%	100%
6	Hue	0 → 360°	0	255	0%	100%	0	65535	0%	100%
7	Saturation	0 → 100 % Saturation	0	255	0%	100%	0	65535	0%	100%

Pulsing

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Speed	5 → 90 Pulses / Min	0	255	0%	100%	0	65535	0%	100%
2	Pulse Duration	4 → 0.25 Seconds	0	255	0%	100%	0	65535	0%	100%
3	Color Temperature	CCT 2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
4	Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
		Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
		-99 % → -1%	21	119	9%	47%	9831	30145	16%	46%
		Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
		1% → 99 %	146	244	58%	96%	39977	60292	62%	92%
	Full Plus Green	245	255	97%	100%	60293	65535	93%	100%	
5	Cross Fade to Color	White → Color	0	255	0%	100%	0	65535	0%	100%
6	Hue	0 → 360°	0	255	0%	100%	0	65535	0%	100%
7	Saturation	0 → 100 % Saturation	0	255	0%	100%	0	65535	0%	100%

Television

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	CCT Range <i>Not continuous, set range for random generation</i>	2.800 K → 4.700 K	0	84	0%	32%	0	21759	0%	32%
		4.700 K → 6.500 K	85	170	33%	66%	21760	43775	33%	66%
		6.500 K → 10.000 K	171	255	67%	100%	43776	65535	67%	100%
2	Sequence	4 → 24 Changes / Min	0	255	0%	100%	0	65535	0%	100%

Explosion

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Decay	Decay 4 → 0.5 Seconds	0	255	0%	100%	0	65535	0%	100%
2	Trigger	Manual (bump intensity to explode)	250	255	98%	100%	64224	65535	98%	100%
3	Color Temperature	CCT 2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
4	Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
		Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
		-99 % → -1%	21	119	9%	47%	9831	30145	16%	46%
		Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
		1% → 99 %	146	244	58%	96%	39977	60292	62%	92%
	Full Plus Green	245	255	97%	100%	60293	65535	93%	100%	
5	Cross Fade to Color	White → Color	0	255	0%	100%	0	65535	0%	100%
6	Hue	0 → 360°	0	255	0%	100%	0	65535	0%	100%
7	Saturation	0 → 100 % Saturation	0	255	0%	100%	0	65535	0%	100%

Fluorescent Flicker

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Sequence	2 → 6 Seconds of Still	0	255	0%	100%	0	65535	0%	100%
2	Speed	3 → 10 Flickers per Second	0	255	0%	100%	0	65535	0%	100%
3	Color Temperature	CCT 2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
4	Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
		Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
		-99 % → -1%	21	119	9%	47%	9831	30145	16%	46%
		Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
		1% → 99 %	146	244	58%	96%	39977	60292	62%	92%
	Full Plus Green	245	255	97%	100%	60293	65535	93%	100%	
5	Cross Fade to Color	White → Color	0	255	0%	100%	0	65535	0%	100%
6	Hue	0 → 360°	0	255	0%	100%	0	65535	0%	100%
7	Saturation	0 → 100 % Saturation	0	255	0%	100%	0	65535	0%	100%

Welding

Parameter	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
			Start	End	Start	End	Start	End	Start	End
1	Sequence	Slow → Fast	0	255	0%	100%	0	65535	0%	100%
2	Min Intensity Level	0 % → 75 % Minimum Intensity Level	0	255	0%	100%	0	65535	0%	100%
3	Color Temperature	CCT 2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
4	Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
		Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
		-99 % → -1%	21	119	9%	47%	9831	30145	16%	46%
		Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
		1% → 99 %	146	244	58%	96%	39977	60292	62%	92%
	Full Plus Green	245	255	97%	100%	60293	65535	93%	100%	
5	Cross Fade to Color	White → Color	0	255	0%	100%	0	65535	0%	100%
6	Hue	0 → 360°	0	255	0%	100%	0	65535	0%	100%
7	Saturation	0 → 100 % Saturation	0	255	0%	100%	0	65535	0%	100%

Variable Channels







Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
14	23	24	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
15	25	26	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
16	27	28	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
17	29	30	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
18	31	32	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
19	33	34	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
20	35	36	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
21	37	38	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel			Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit			
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End		
ECC	ECC		Fan Control	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-		
OFF	OFF		<i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>		Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-	
14	23				Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-	
					High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-	
ECC	ECC				Reserved	154	201	61%	78%	-	-	-	-	
ON	ON				Fan at Full Speed	202	249	79%	98%	-	-	-	-	
22	39				Fan Off	250	255	99%	100%	-	-	-	-	
ECC	ECC			Favorites	No Effect	0	9	1*	-	-	-	-	-	
OFF	OFF		User Defined Favorites		Favorite 01	10	-	-	-	-	-	-	-	
15	24				Favorite 02	11	-	-	-	-	-	-	-	
					Favorite 03	12	-	-	-	-	-	-	-	
ECC	ECC				Favorite 04	13	-	-	-	-	-	-	-	
ON	ON				Favorite 05	14	-	-	-	-	-	-	-	
23	40				Favorite 06	15	-	-	-	-	-	-	-	
					-	-	-	-	-	-	-	
				Favorite 246	255	-	-	-	-	-	-	-		
ECC	ECC		Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-		
OFF	OFF				1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-	
16	25													
ECC	ECC		Color Sensor	Off	0	19	0%	7%	-	-	-	-		
OFF	OFF			<i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Continuous	20	127	8%	50%	-	-	-	-	
17	26					Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC	ECC													
ON	ON													
25	42													
ECC	ECC		Sync	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-		
OFF	OFF			<i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Sync Mode OFF	20	39	8%	15%	-	-	-	-	
18	27					Sync Mode ON	40	59	16%	23%	-	-	-	-
						Reserved	60	255	24%	100%	-	-	-	-
ECC	ECC		(No Effect / Reverts to internal setting)											
ON	ON													
26	43													

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)



Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 13: 8 Bit
Mode 14: 16 Bit

Fixed Channels

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03/04		Intensity Red	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
03	05/06		Intensity Green	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
04	07/08		Intensity Blue	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
05	09/10		Intensity Amber	0 % → 100 % (Only used when Calibration is "Off" in RGBACL mode)	0	255	0%	100%	0	65535	0%	100%
06	11/12		Intensity Cyan	0 % → 100 % (Only used when Calibration is "Off" in RGBACL mode)	0	255	0%	100%	0	65535	0%	100%
07	13/14		Intensity Lime	0 % → 100 % (Only used when Calibration is "Off" in RGBACL mode)	0	255	0%	100%	0	65535	0%	100%
08	15/16		Intensity White	0 % → 100 % (Only used when Calibration is "On" in RGBACL mode)	0	255	0%	100%	0	65535	0%	100%
09	17/18		CCT value for calibrated RGBW white point	(Only used when Calibration is "On" in RGBACL mode)	-	-	0%	100%	-	-	0%	100%
10	19/20		G/M value for calibrated RGBW white point	(Only used when Calibration is "On" in RGBACL mode)	-	-	0%	100%	-	-	0%	100%
11	21		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
12	22		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
13	23		Reserved	-	0	255	0%	100%	-	-	-	-

Variable Channels

Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
14	24	25	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
15	26	27	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
16	28	29	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
17	30	31	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
18	32	33	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
19	34	35	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
20	36	37	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
21	38	39	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
ECC	ECC		Fan Control <i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-
OFF	OFF			Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-
14	24			Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-
				High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-
ECC	ECC			Reserved	154	201	61%	78%	-	-	-	-
ON	ON			Fan at Full Speed	202	249	79%	98%	-	-	-	-
22	40		Fan Off	250	255	99%	100%	-	-	-	-	
ECC	ECC		Favorites User Defined Favorites	No Effect	0	9	1*	-	-	-	-	-
OFF	OFF			Favorite 01	10	-	-	-	-	-	-	-
15	25			Favorite 02	11	-	-	-	-	-	-	-
				Favorite 03	12	-	-	-	-	-	-	-
ECC	ECC			Favorite 04	13	-	-	-	-	-	-	-
ON	ON			Favorite 05	14	-	-	-	-	-	-	-
23	41			Favorite 06	15	-	-	-	-	-	-	-
				-	-	-	-	-	-	-
		Favorite 246	255	-	-	-	-	-	-	-		
ECC	ECC		Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-
OFF	OFF			1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-
16	26											
ECC	ECC		Color Sensor <i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Off	0	19	0%	7%	-	-	-	-
OFF	OFF			Continuous	20	127	8%	50%	-	-	-	-
17	27			Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC	ECC		Sync <i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-
OFF	OFF			Sync Mode OFF	20	39	8%	15%	-	-	-	-
18	28			Sync Mode ON	40	59	16%	23%	-	-	-	-
ECC	ECC			Reserved (No Effect / Reverts to internal setting)	60	255	24%	100%	-	-	-	-
ON	ON											
26	44											

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)



Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 15: 8 Bit
Mode 16: 16 Bit

Fixed Channels

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03/04		Color Temperature CCT	2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
03	05/06		Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
				Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
				-99 % → -1 %	21	119	9%	47%	9831	30145	16%	46%
				Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
				1 % → 99 %	146	244	58%	96%	39977	60292	62%	92%
				Full Plus Green	245	255	97%	100%	60293	65535	93%	100%
04	07/08		Cross Fade to Color	White → HSI Color	0	255	0%	100%	0	65535	0%	100%
05	09/10		Hue	0° → 360°	0	255	0%	100%	0	65535	0%	100%
06	11/12		Saturation	0 → Full Saturation	0	255	0%	100%	0	65535	0%	100%
07	13		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
08	14		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
09	15		Reserved	-	0	255	0%	100%	-	-	-	-

Variable Channels

Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
10	16	17	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
11	18	19	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
12	20	21	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
13	22	23	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
14	24	25	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
15	26	27	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
16	28	29	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
17	30	31	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
ECC	ECC		Fan Control <i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-
OFF	OFF			Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-
10	16			Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-
				High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-
ECC	ECC			Reserved	154	201	61%	78%	-	-	-	-
ON	ON			Fan at Full Speed	202	249	79%	98%	-	-	-	-
18	32		Fan Off	250	255	99%	100%	-	-	-	-	
ECC	ECC		Favorites User Defined Favorites	No Effect	0	9	1*	-	-	-	-	-
OFF	OFF			Favorite 01	10	-	-	-	-	-	-	-
11	17			Favorite 02	11	-	-	-	-	-	-	-
				Favorite 03	12	-	-	-	-	-	-	-
ECC	ECC			Favorite 04	13	-	-	-	-	-	-	-
ON	ON			Favorite 05	14	-	-	-	-	-	-	-
19	33			Favorite 06	15	-	-	-	-	-	-	-
				-	-	-	-	-	-	-
		Favorite 246	255	-	-	-	-	-	-	-		
ECC	ECC		Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-
OFF	OFF			1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-
12	18											
ECC	ECC		Color Sensor <i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Off	0	19	0%	7%	-	-	-	-
OFF	OFF			Continuous	20	127	8%	50%	-	-	-	-
13	19			Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC	ECC	21	35									
ECC	ECC		Sync <i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-
OFF	OFF			Sync Mode OFF	20	39	8%	15%	-	-	-	-
14	20			Sync Mode ON	40	59	16%	23%	-	-	-	-
ECC	ECC			Reserved (No Effect / Reverts to internal setting)	60	255	24%	100%	-	-	-	-
ON	ON	22	36									

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)






Product Line: **Orbiter**
 Mode Version: **5.0**

Mode 17: 8 Bit
Mode 18: 16 Bit




Fixed Channels

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
01	01/02		Dimmer	Closed → Open	0	255	0%	100%	0	65535	0%	100%
02	03		Color Mode Selection	CCT & Green - Magenta Point	0	9	0%	4%	-	-	-	-
				HSI	10	19	5%	7%	-	-	-	-
				Calibrated RGBW / Direct RGBACL	20	29	8%	11%	-	-	-	-
				Gel Selection	30	39	12%	16%	-	-	-	-
				Source Matching	40	49	17%	19%	-	-	-	-
				x, y Coordinates	50	59	20%	23%	-	-	-	-
				Effects	60	69	24%	27%	-	-	-	-
				Reserved	70	255	28%	100%	-	-	-	-
03	04/05		Color Parameter 1	See Table Below	-	-	-	-	-	-	-	
04	06/07		Color Parameter 2	See Table Below	-	-	-	-	-	-		
05	08/09		Color Parameter 3	See Table Below	-	-	-	-	-	-		
06	10/11		Color Parameter 4	See Table Below	-	-	-	-	-	-		
07	12/13		Color Parameter 5	See Table Below	-	-	-	-	-	-		
08	14/15		Color Parameter 6	See Table Below	-	-	-	-	-	-		
09	16/17		Color Parameter 7	See Table Below	-	-	-	-	-	-		
10	18/19		Color Parameter 8	See Table Below	-	-	-	-	-	-		
11	20/21		Color Parameter 9	See Table Below	-	-	-	-	-	-		
12	22/23		Cross Fade to Mode 2	Mode 1 → Mode 2	0	255	-	-	0	65535	-	-
13	24		Color Mode Selection	CCT & Green - Magenta Point	0	9	0%	4%	-	-	-	-
				HSI	10	19	5%	7%	-	-	-	-
				Calibrated RGBW / Direct RGBACL	20	29	8%	11%	-	-	-	-
				Gel Selection	30	39	12%	16%	-	-	-	-
				Source Matching	40	49	17%	19%	-	-	-	-
				x, y Coordinates	50	59	20%	23%	-	-	-	-
				Effects	60	69	24%	27%	-	-	-	-
				Reserved	70	255	28%	100%	-	-	-	-
14	25/26		Color Parameter 1	See Table Below	-	-	-	-	-	-		
15	27/28		Color Parameter 2	See Table Below	-	-	-	-	-	-		
16	29/30		Color Parameter 3	See Table Below	-	-	-	-	-	-		
17	31/32		Color Parameter 4	See Table Below	-	-	-	-	-	-		
18	33/34		Color Parameter 5	See Table Below	-	-	-	-	-	-		
19	35/36		Color Parameter 6	See Table Below	-	-	-	-	-	-		
20	37/38		Color Parameter 7	See Table Below	-	-	-	-	-	-		
21	39/40		Color Parameter 8	See Table Below	-	-	-	-	-	-		
22	41/42		Color Parameter 9	See Table Below	-	-	-	-	-	-		
23	43		Zoom	No Effect	0	19	0%	7%	-	-	-	-
				Linear Spot - Flood (e.g. 20 [15°] ... 255 [30°])	20	255	8%	100%	-	-	-	-
24	44		Focus	No Effect	0	19	0%	7%	-	-	-	-
				Linear Focus	20	255	8%	100%	-	-	-	-
25	45		Reserved	-	0	255	0%	100%	-	-	-	-








CCT & Green - Magenta Point

Parameter		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
				Start	End	Start	End	Start	End	Start	End
1		CCT Range	2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
2		Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
			Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
			-99 % → -1 %	21	119	9%	47%	9831	30145	16%	46%
			Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
			1 % → 99 %	146	244	58%	96%	39977	60292	62%	92%
			Full Plus Green	245	255	97%	100%	60293	65535	93%	100%











HSI

Parameter		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
				Start	End	Start	End	Start	End	Start	End
1		Hue	0 ° → 360°	0	255	0%	100%	0	65535	0%	100%
2		Saturation	0 → Full Saturation	0	255	0%	100%	0	65535	0%	100%

Calibrated RGBW

Parameter		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
				Start	End	Start	End	Start	End	Start	End
1		Intensity Red	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
2		Intensity Green	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
3		Intensity Blue	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
7		Intensity White	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
8		White Point CCT	2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
9		White Point - Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
			Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
			-99 % → -1 %	21	119	9%	47%	9831	30145	16%	46%
			Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
			1 % → 99 %	146	244	58%	96%	39977	60292	62%	92%
			Full Plus Green	245	255	97%	100%	60293	65535	93%	100%

Direct RGBACL

Parameter		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
				Start	End	Start	End	Start	End	Start	End
1		Intensity Red	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
2		Intensity Green	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
3		Intensity Blue	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
4		Intensity Amber	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
5		Intensity Cyan	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
6		Intensity Lime	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
7		Intensity White	0 % → 100 %	0	255	0%	100%	0	65535	0%	100%
8		White Point CCT	2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%
9		White Point - Green - Magenta Point	Neutral / No Effect	0	10	0%	4%	0	4587	0%	7%
			Full Minus Green	11	20	5%	8%	4588	9830	8%	15%
			-99 % → -1 %	21	119	9%	47%	9831	30145	16%	46%
			Neutral / No Effect	120	145	48%	57%	30146	39976	47%	61%
			1 % → 99 %	146	244	58%	96%	39977	60292	62%	92%
			Full Plus Green	245	255	97%	100%	60293	65535	93%	100%

Gel Selection

Parameter	Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit		
				Start	End	Start	End	Start	End	Start	End	
1	GEL	Gel, CCT Selection	2.000 K → 20.000 K	0	255	0%	100%	0	65535	0%	100%	
2	GEL	Gel, Color Matching Selection	Best Color	0	84	0%	33%	0	21759	0%	33%	
			<i>Note: Color Quality Optimized</i>									
			Brightest	85	170	34%	67%	21760	43775	34%	67%	
			<i>Note: Color Brightness Optimized</i>									
			No Color Gel	171	255	68%	100%	43776	65535	68%	100%	
3	GEL	Gel, Brand	Rosco	0	127	0%	50%	0	32767	0%	50%	
			LEE Filters	128	255	51%	100%	32768	65535	51%	100%	
4	GEL	Gel, Category (Brand Dependent)	Choose Gel Manufacturer on parameter 3									
			Category 1	0	50	0%	20%	0	13055	0%	20%	
			Rosco: Color Correction									
			LEE: Color Correction									
			Category 2	51	101	21%	39%	13056	26111	21%	39%	
			Rosco: CalColor									
LEE: Color Filters												
Category 3	102	152	40%	60%	26112	39167	40%	60%				
Rosco: Storaro Selection												
LEE: 600 Series												
Category 4	153	203	61%	80%	39168	52223	61%	80%				
Rosco: Cinelux --> Roscolux												
LEE: Cosmetic Filters												
Category 5	204	255	81%	100%	52224	65535	81%	100%				
LEE: 700 Series												
5	GEL	Gel	See "Gels" Table	0	255	0%	100%	0	65535	0%	100%	











Source Matching

Parameter	Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
				Start	End	Start	End	Start	End	Start	End
1	Lightbulb	Category	Incandescent	0	50	0%	20%	0	13055	0%	20%
			Fluorescent	51	101	21%	39%	13056	26111	21%	39%
			Discharge	102	152	40%	59%	26112	39167	40%	59%
			Other	153	203	60%	79%	39168	52223	60%	79%
			Reserved for Future Use	204	255	80%	100%	52224	65535	80%	100%
2	Flame	Source	See "Source" Table	0	255	0%	100%	0	65535	0%	100%

x, y Coordinates

Parameter	Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
				Start	End	Start	End	Start	End	Start	End
1	X	X Coordinate	0.0 - 0.8	0	255	0%	100%	0	65535	0%	100%
2	Y	Y Coordinate	0.0 - 0.8	0	255	0%	100%	0	65535	0%	100%

Effects

Parameter		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
				Start	End	Start	End	Start	End	Start	End
1		Effect Selection	No Effect	0	9	0%	4%	0	2304	0%	4%
			Party Effect	10	19	5%	7%	2305	4864	5%	7%
			Candle	20	29	8%	11%	4865	7424	8%	11%
			Clouds Passing	30	39	12%	15%	7425	9984	12%	15%
			Club Lights	40	49	16%	19%	9985	12544	16%	19%
			Cop Car	50	59	20%	23%	12545	15104	20%	23%
			Fire	60	69	24%	27%	15105	17664	24%	27%
			Fireworks	70	79	28%	31%	17665	20224	28%	31%
			Light Strobe	80	89	32%	35%	20225	22784	32%	35%
			Lightning	90	99	36%	39%	22785	25344	36%	39%
			Paparazzi	100	109	40%	43%	25345	27904	40%	43%
			Pulsing	110	119	44%	47%	27905	30464	44%	47%
			Television	120	129	48%	51%	30465	33024	48%	51%
			Explosion	130	139	52%	55%	33025	35584	52%	55%
			Fluorescent Flicker	140	149	56%	58%	35585	38144	56%	58%
Welding	150	159	59%	62%	38145	40704	59%	62%			
		Reserved for Future Use	160	255	63%	100%	40705	65535	63%	100%	
2		Effect Parameter 1	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
3		Effect Parameter 2	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
4		Effect Parameter 3	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
5		Effect Parameter 4	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
6		Effect Parameter 5	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
7		Effect Parameter 6	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
8		Effect Parameter 7	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%
9		Effect Parameter 8	See "Effects" Table	0	255	0%	100%	0	65535	0%	100%

Variable Channels

Extended Color Control (ECC)

If the DMX setting "ECC" is "OFF", the following channels shall be automatically eliminated from all DMX modes

8 Bit	16 Bit		Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
	HI	LO			Start	End	Start	End	Start	End	Start	End
26	46	47	Warmer / Cooler	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Cool (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Warm (+1.000)	148	255	58%	100%	37780	65535	58%	100%
27	48	49	Saturate / Desaturate	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full Desaturate (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full Saturate (+1.000)	148	255	58%	100%	37780	65535	58%	100%
28	50	51	+ Red / - Red	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Red (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Red (+1.000)	148	255	58%	100%	37780	65535	58%	100%
29	52	53	+ Green / - Green	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Green (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Green (+1.000)	148	255	58%	100%	37780	65535	58%	100%
30	54	55	+ Blue / - Blue	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Blue (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Blue (+1.000)	148	255	58%	100%	37780	65535	58%	100%
31	56	57	+ Cyan / - Cyan	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Cyan (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Cyan (+1.000)	148	255	58%	100%	37780	65535	58%	100%
32	58	59	+ Magenta / - Magenta	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Magenta (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Magenta (+1.000)	148	255	58%	100%	37780	65535	58%	100%
33	60	61	+ Yellow / - Yellow	Neutral	0	19	0%	7%	0	4883	0%	7%
				Full -Yellow (-1.000) → Neutral (0.000)	20	127	8%	50%	4884	32767	8%	50%
				Neutral	128	147	51%	57%	32768	37779	51%	57%
				Neutral (0.000) → Full +Yellow (+1.000)	148	255	58%	100%	37780	65535	58%	100%

Operation

If the DMX setting "Operation" is "OFF", the following channels shall be automatically eliminated from all DMX modes

DMX Channel		Icon	Parameter Name	Function	Value 8 Bit		% 8 Bit		Value 16 Bit		% 16 Bit	
8 Bit	16 Bit				Start	End	Start	End	Start	End	Start	End
ECC	ECC		Fan Control <i>Note: Fan Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Use Fan Mode Setting of Fixture Menu	0	9	0%	3%	-	-	-	-
OFF	OFF			Quiet, Fan Speed Fixed	10	57	4%	22%	-	-	-	-
26	46			Variable, Fan Speed Variable	58	105	23%	41%	-	-	-	-
				High Temp, Fan Speed Fixed	106	153	42%	60%	-	-	-	-
ECC	ECC			Reserved	154	201	61%	78%	-	-	-	-
ON	ON			Fan at Full Speed	202	249	79%	98%	-	-	-	-
34	62		Fan Off	250	255	99%	100%	-	-	-	-	
ECC	ECC		Favorites	No Effect	0	9	1*	-	-	-	-	-
OFF	OFF		User Defined Favorites	Favorite 01	10	-	-	-	-	-	-	-
27	47			Favorite 02	11	-	-	-	-	-	-	-
				Favorite 03	12	-	-	-	-	-	-	-
ECC	ECC			Favorite 04	13	-	-	-	-	-	-	-
ON	ON			Favorite 05	14	-	-	-	-	-	-	-
35	63			Favorite 06	15	-	-	-	-	-	-	-
				-	-	-	-	-	-	-
		Favorite 246		255	-	-	-	-	-	-	-	
ECC	ECC		Light Strobe ²	No Effect	0	19	0%	7%	-	-	-	-
OFF	OFF			1 Flash / s → 25 Flashes / s	20	255	8%	100%	-	-	-	-
28	48											
ECC	ECC		Color Sensor <i>Note: Color Sensor Mode reverts to fixture menu setting, when DMX signal is lost.</i>	Off	0	19	0%	7%	-	-	-	-
OFF	OFF			Continuous	20	127	8%	50%	-	-	-	-
29	49			Momentary - Once Activated	128	255	51%	100%	-	-	-	-
ECC	ECC											
ON	ON											
37	65											
ECC	ECC		Sync <i>Note: Sync Mode reverts to fixture menu setting, when DMX signal is lost.</i>	No Effect / Reverts to internal setting	0	19	0%	7%	-	-	-	-
OFF	OFF			Sync Mode OFF	20	39	8%	15%	-	-	-	-
30	50			Sync Mode ON	40	59	16%	23%	-	-	-	-
				Reserved	60	255	24%	100%	-	-	-	-
ECC	ECC			(No Effect / Reverts to internal setting)								
ON	ON											
38	66											

* Providing a percentage less than "1" is not possible

² Not available in DMX Effect Mode

[See page 5 for more information.](#)

**CCT Conversion**8 Bit

$$\text{DMX Value} = \frac{\text{Desired CCT} - 2000}{70.588}$$

$$\text{CCT} = (\text{DMX Value} * 70.588) + 2000$$

16 Bit

$$\text{DMX Value} = \frac{\text{Desired CCT} - 2000}{0.27466239}$$

$$\text{CCT} = (\text{DMX Value} * 0.27466239) + 2000$$

x, y Coordinate to DMX Value Conversion8 Bit

$$\text{DMX}_x = \frac{x_{\text{value}} * 255}{0.8}$$

$$\text{DMX}_y = \frac{y_{\text{value}} * 255}{0.8}$$

16 Bit

$$\text{DMX}_x = \frac{x_{\text{value}} * 65535}{0.8}$$

$$\text{DMX}_y = \frac{y_{\text{value}} * 65535}{0.8}$$

ARRI 