




# CERTIFICATE

No. U8 06 06 13563 034

**Holder of Certificate:** Arnold & Richter Cine Technik GmbH & Co Betriebs KG

Pulvermühle  
83071 Stephanskirchen  
GERMANY

**Certification Mark:**



**Product:** Luminaires  
(Daylight luminaires for professional use)

The product was voluntarily tested according to the relevant safety requirements and mentioned properties. It can be marked with the certification mark shown above. See also notes overleaf.

**Test report no.:** 028-70077972-000

**Date,** 2006-06-27

Page 1 of 2





**CERTIFICATE**  
**No. U8 06 06 13563 034**

**Model(s):** Type: ARRI X 12 models: L1.822xx.y  
 Type: ARRI X 40/25 models: L1.824xx.y  
 Type: ARRI X 60 models: L1.826xx.y  
 Remark:  
 (Where x can be any number based on id.-no added with a value between 00 and 25 and describes mostly the color of the housing. Where y can be any letter and describes the different versions of design.)  
 Type: ARRI X Ceramic 250 models: L1.8620x.y  
 Remark:  
 (Where x can be any number based on id.-no added with a value between 0 and 5 and describes mostly the color of the housing. Where y can be any letter but "A" and "J" and describes the different versions of design.)

**Brand Name:** **ARRI**

**Parameters:**

Rated voltage:	ARRI X 12:	100 V
	ARRI X 40/25:	115 V
	ARRI X 40/25:	200 V
	ARRI X 60:	123 V
	ARRI X Ceramic 250:	117-240 V
Rated power /	ARRI X 12:	1200 W / 13,8 A
Rated current:	ARRI X 40/25:	2500 W / 25,6 A (with 2500 W lamp)
	ARRI X 40/25:	4000 W / 24,0 A (with 4000 W lamp)
	ARRI X 60:	6000 W / 55,0 A
	ARRI X Ceramic 250:	250 W / 3,0 A
Rated frequency:	50 to 100 Hz all but ARRI X Ceramic 250 50/60 Hz only ARRI X Ceramic 250	
Protection class:	I	
Degree of protection:	IP23 (All but ARRI X Ceramic 250) IP20 (Only ARRI X Ceramic 250)	

**Tested according to:** UL 1573:2003  
 CAN/CSA C22.2 No. 166-M1983  
 CAN/CSA C22.2 No. 9-M1989

**Production Facility(ies):** 13563