

ARRILITE PLUS LAMPHEADS

TECHNICAL DATA



ARRILITE Plus Lamphead / Versions	ARRILITE 750 Plus	ARRILITE 2000 Plus
Ident-No.	L0.0034720* *incl. 4-leaf barndoor and accessory holder	L0.0034722** **incl. 4-leaf barndoor
Main Features		
Type of Lamphead	Open Face	Open Face
Reflector	MAX Technology Facetted Reflector	MAX Technology Facetted Reflector
Wattage	750 W	2000 W
Lamp Type	HPL* 750 W, 575 W, 375 W GKV** 600 W, FKR 650 W	FEX 2000 W / 230 V FEY 2000 W / 120 V
Lamp Base	G9,5	RX7s
UV Protection Glass Diameter	142.7 mm / 5.7"	215 mm / 8.5"
Color	blue / silver	blue / silver
Further Versions	also available in Schuko and 120 V version	also available in Schuko and 120 V version
Technical Data of the Luminaire		
Max. Operating Temperature	ta= 45° C / 113° F	ta= 45° C / 113° F
Max. Surface Temperature	tc= 180° C / 356° F	tc= 200° C / 392° F
Tolerable Inclination	max. 90° upwards / max. 90° downwards	max. 90° upwards / max. 90° downwards
Safe Distances	4 m / 13.2 ft. to illuminated surface 0.5 m / 1.7 ft. around the luminaire	6 m / 19.7 ft. to illuminated surface 0.5 m / 1.7 ft. around the luminaire
Protective Class	I - Protective Earth	I - Protective Earth
Protective Rate	IP20	IP20
Specifications		
Dimensions (H x W x L)	230 x 230 x 233 mm / 9.0 x 9.1 x 9.2"	376 x 355 x 241 mm / 14.8 x 14.0 x 9.5"
Packed Size (H x W x L)	260 x 230 x 290 mm / 10.3 x 9.1 x 11.5"	375 x 345 x 320 mm / 14.8 x 13.6 x 12.6"
Weight	approx. 2.2 kg (4.72 lbs)	approx. 3.8 kg (8.17 lbs)
Packed Weight	approx. 2.6 kg (5.56 lbs)	approx. 4.3 kg (9.34 lbs)
Mounting	Socket 16 mm / 5/8" (0.63")	Socket 16 mm / 5/8" (0.63")
Certification	CE, UKCA, CB, ENEC, cNRTLus	CE, UKCA, CB, ENEC, cNRTLus
Accessories		
Accessory diameter	168 mm (6.6")	235 mm (9.3") / 254 mm (10.0")
	4-leaf barndoor Scrim Chimera Lightbank	4-leaf barndoor Scrim Chimera Lightbank Speed ring circular
Photometrical Data		
Distance	4 m (13 ft.) [Output / diameter]	6 m (20 ft.) [Output / diameter]
Spot	18.0°: 1,881 lux / Ø 1.27 m	20.0°: 3,715 lux / Ø 2.12 m
Medium	30.0°: 494 lux / Ø 2.14 m	-
Flood	66.0°: 269 lux / Ø 5.20 m	53.0°: 764 lux / Ø 5.98 m
Distance	8 m (26 ft.) [Output / diameter]	8 m (26 ft.) [Output / diameter]
Spot	18.0°: 470 lux / Ø 2.53 m	20.0°: 2,090 lux / Ø 2.82 m
Medium	30.0°: 123 lux / Ø 4.29 m	-
Flood	66.0°: 67 lux / Ø 10.39 m	53.0°: 430 lux / Ø 7.98 m
Distance	10 m (33 ft.) [Output / diameter]	10 m (33 ft.) [Output / diameter]
Spot	18.0°: 301 lux / Ø 3.17 m	20.0°: 1,338 lux / Ø 3.53 m
Medium	30.0°: 79 lux / Ø 5.36 m	-
Flood	66.0°: 43 lux / Ø 12.99 m	53.0°: 275 lux / Ø 9.97 m

All specifications are nominal / typical values.

80.0034165 as of June 2022 - Design and specifications are subject to change without notice.



For light output at any distance use our ARRI Photometrics App.

Please visit our website for the latest downloads and to find more information about the ARRILITE Plus: www.arri.com

