

# External Radio Module ERM - Sample Configurations for CSS



Configuration Overview | 8.5.1 / 2021.02

## Digital Encoder Head or Wheels with ERM LCS



ERM LBUS to FS CAN Bus Adapter Cable, 0.2m/0.65ft  
[K2.0036903](#)


Extension cable



or



Required EXTENSION CABLES:  
SRH FS CAN Bus Cable, 1m/3.2ft, [K2.0033762](#)  
SRH FS CAN Bus Cable, 10m/32.8ft, [K2.0019302](#)  
SRH FS CAN Bus Cable, 25m/82ft, [K2.0019301](#)  
recommended: 1m legal distance



Extension cable



Cable LBUS - D-Tap (1.2m/4ft)  
[K2.0006757](#)



12V Battery Power Cable, D-Tab, 4pin XLR, 1.5m/5ft,  
[K2.0021422](#)

any small Battery with D-Tap socket

## Stabilized Remote Head with ERM SRH



SRH-3 FS CAN Bus Cable, 1m/3.2ft, [K2.0033762](#)

Extension cable




SRH High Capacity Battery Power Cable, 24V, 3pin XLR, 10m/33ft, [K2.0021427](#)

SRH High Capacity Battery Power Cable, 12V, 4pin XLR, 10m/33ft, [K2.0021428](#)



Battery [www.antonbauer.com](#)

Required EXTENSION CABLES:  
SRH FS CAN Bus Cable, 1m/3.2ft, [K2.0033762](#)  
SRH FS CAN Bus Cable, 10m/32.8ft, [K2.0019302](#)  
SRH FS CAN Bus Cable, 25m/82ft, [K2.0019301](#)



Extension cable



12V Battery Power Cable, D-Tab, 4pin XLR, 1.5m/5ft,  
[K2.0021422](#)



any small Battery with D-Tap socket