cmotion cdistance

Configuration Overview | 4.8.1 / 2025.10

cmotion cdistance

cmotion cfinder III

cmotion cdistance
K2.0015667

LBUS

LBUS 0.2m/8“, K2.0006749
LBUS 0.3m/1ft, K2.0006750
LBUS 0.5m/1.5ft, K2.0006751
LBUS 0.8m/2.5ft, K2.0006752
LBUS 1.5m/5ft, K2.0006753
LBUS 3m/10ft, K2.0006754
LBUS 6m/20ft, K2.0006755
LBUS 15m/49ft, K2.0006756

cforce motor

ALEXA Mini /
ALEXA Mini LF

Focus Tracking

UDM values / Lens Data

LBUS Serial LBUS

LBUS Cable

Cable UDM-ALEXA (1,5m/5ft)
K2.65261.0 (yellow cable)
Connects to EXT socket of ALEXA
cameras with SUP 8.0 or later

EXT

ALEXA

UDM values / Lens Data

Focus Tracking

WCU-4

Wireless Compact Unit
WCU-4, K2.72103.0

cdistance readout

Cable UDM-SERIAL (1,5m/5ft)
K2.65144.0 (yellow cable)

Serial

UMC-4

UDM values / Lens Data

Focus Tracking

Cable LBUS - RS (0.8m/2.6ft)
K2.0006759

RS

any camera
with RS

AMIRA

UDM values /
no Lens Data

SMC/EMC/AMC to RS, K2.0001606

CAM

LBUS

AMC-1

LBUS 0.2m/8“, K2.0006749
LBUS 0.3m/1ft, K2.0006750
LBUS 0.5m/1.5ft, K2.0006751
LBUS 0.8m/2.5ft, K2.0006752
LBUS 1.5m/5ft, K2.0006753
LBUS 3m/10ft, K2.0006754
LBUS 6m/20ft, K2.0006755
LBUS 15m/49ft, K2.0006756

cforce motors

LBUS LBUS

additional power might be needed:

Cable LBUS to D-Tap 1.2m/4ft
K2.0006757
Cable LBUS to D-Tap 0.8m/2.5ft
K2.0006758
Cable LBUS to RS 0.8m/2.5ft
K2.0006759
Cable LBUS to XLR-4 0.8m/2.5ft
K2.0006760

© 2025 Arnold & Richter Cine Technik GmbH & Co. Betriebs KG. All rights reserved. This material is provided “as is” for information purposes only without any warranty. ARRI assumes no responsibility with regard to the performance or use of the products or typographical errors or inaccuracies of given information. Product specifications are subject to change without notice. For a full listing of all available components consult the price list.