

Stabilizer System - Cable Guide 5



Configuration Overview | 8.6.4 / 2024.08

Item Number	Cable Name	Supported Cameras	Artemis 1	Artemis 2	TRINITY 1	TRINITY 2	360 EVO
K2.0019303	SRH Power Supply Power and Data Cable, 12V/24V, 20m/65.6ft	Power and data cable to power the Stabilized Remote Head 360 EVO, SRH-3 and SRH360 from the 600 W SRH Power Supply K0.0019478 with 12 V and 24 V. 12V/24V high-capacity camera power, plus FS CAN bus. Length: 20m/65.6ft	✗	✗	✗	✓ PAN Axis only	✓
K2.0033761	ERM Power Cable, ERM-2400 & ERM-900	Spare ERM Power Cable for ERM-2400 & ERM-900 Length: 30cm / 11.8in"	✗	✗	✗	✓	✓
K2.0036900	ERM LCS to FS CAN Bus Adapter Cable, 0.2m/0.65ft	Adapter cable to connect the ERM LCS to the WCU-4, SXU-1 UMC-4 and ALEXA Plus camera via the LCS socket.	✗	✗	✗	✓	✓
K2.0036903	ERM LBUS to FS CAN Bus Adapter Cable, 0.2m/0.65ft	Adapter cable to connect the ERM LCS to Master Grips, OCU-1, DRW-1 and DEH-1 via the LBUS socket	✗	✗	✗	✓	✓
K2.0036901	ERM EXT. to FS CAN Bus Adapter Cable, 0.2m/0.65ft	Adapter cable to connect the ERM LCS to ALEXA Mini, ALEXA Mini LF and Amira via the EXT. socket.	✗	✗	✗	✓	✓
K2.0036902	ERM D-Tap Pwr Cable, 0B Lemo 2-pin to D-Tap, 1m/3.2ft	Power cable D-Tap to 2-pin Lemo 0B. Length: 1m/3.2ft	✗	✗	✗	✓	✓
K2.0041984	12G HD SDI BNC Cable, 0,63m/25in	12G HD SDI BNC Cable, Length: 0,63m/25in	✓	✓	✓	✓	✓
K2.0044234	12G HD SDI BNC Cable, 0,84m/33in	12G HD SDI BNC Cable, Length: 0,84m/33in	✓	✓	✓	✓	✓
K2.0051086	12G HD SDI BNC Cable, 1,3m/51,2in	12G HD SDI BNC Cable, Length: 0,84m/33in	✓	✓	✓	✓	✓
K2.0014804	TRINITY BNC Cable for Joystick Main Cable	Spare BNC-SMB cable for the TRINITY Joystick Main Cable	✗	✗	✓	✗	✗
K2.0010482	Tally Sensor Cable, Gen.1 & 2	Tally Sensor Cable can be used with the first and second generation of the Tally system. Lemo 0S 4pin Length: 0,55m / 1.80 ft	✓	✓	✓	✓	✗
K2.0047301	Tally Gen. 2 Cable CCP Live	Power / Tally cable that connects the Tally host module to CCP Live. Lemo 0S 4pin to 0S 4pin Length: 0,55m / 1.80 ft	✓	✓	✓	✓	✗