







# Camera Product Comparison - ALEXA Models



CONFIGURATION OVERVIEW – 1.1.2 / 2018.03

© 2010 Arnold & Richter Cine Technik GmbH & Co. Betriebs KG. All rights reserved. This material is provided "as is" for information purposes only without any warranty. ARRI assumes no responsibility with regard to the performance or use of the products or typographical errors or inaccuracies of given information. Product specifications are subject to change without notice. For a full listing of all available components consult the price list.

Camera Model / Weight	Shutter Range	Sensor Mode	Sound Level at 24 fps & Camera Speeds in Frames per Second	Lens Data System												
 <p><b>ALEXA Mini</b> 2,3 kg / 5 lbs</p>	5° – 356° electronic shutter	16:9 4:3	<table border="1"> <tr> <td>&lt;20 db/A</td> <td>0,75</td> <td>200</td> </tr> <tr> <td>&lt;20 db/A</td> <td>0,75</td> <td>150</td> </tr> </table>	<20 db/A	0,75	200	<20 db/A	0,75	150	YES YES						
<20 db/A	0,75	200														
<20 db/A	0,75	150														
 <p><b>ALEXA Classic EV</b> 6,3 kg / 13,8 lbs (1)</p>	5° – 358° electronic shutter	16:9	<table border="1"> <tr> <td>&lt;20 db/A</td> <td>0,75</td> <td>60 ... 120 (2)</td> </tr> </table>	<20 db/A	0,75	60 ... 120 (2)	NO									
<20 db/A	0,75	60 ... 120 (2)														
 <p><b>ALEXA SXT EV</b> 6,5 kg / 14,3 lbs (3)</p>  <p><b>ALEXA SXT Plus</b> 6,9 kg / 15,2 lbs (3)</p>	5° – 358° electronic shutter	16:9 6:5 4:3 Open Gate	<table border="1"> <tr> <td>&lt;19 db/A</td> <td>0,75</td> <td>120</td> </tr> <tr> <td>&lt;19 db/A</td> <td>0,75</td> <td>96</td> </tr> <tr> <td>&lt;19 db/A</td> <td>0,75</td> <td>96</td> </tr> <tr> <td>&lt;19 db/A</td> <td>0,75</td> <td>75</td> </tr> </table>	<19 db/A	0,75	120	<19 db/A	0,75	96	<19 db/A	0,75	96	<19 db/A	0,75	75	YES YES YES YES
<19 db/A	0,75	120														
<19 db/A	0,75	96														
<19 db/A	0,75	96														
<19 db/A	0,75	75														
 <p><b>ALEXA SXT W</b> 7,3 kg / 16,1 lbs (3)</p>	5° – 358° electronic shutter	16:9 6:5 4:3 Open Gate	<table border="1"> <tr> <td>&lt;19 db/A</td> <td>0,75</td> <td>120</td> </tr> <tr> <td>&lt;19 db/A</td> <td>0,75</td> <td>96</td> </tr> <tr> <td>&lt;19 db/A</td> <td>0,75</td> <td>96</td> </tr> <tr> <td>&lt;19 db/A</td> <td>0,75</td> <td>75</td> </tr> </table>	<19 db/A	0,75	120	<19 db/A	0,75	96	<19 db/A	0,75	96	<19 db/A	0,75	75	YES YES YES YES
<19 db/A	0,75	120														
<19 db/A	0,75	96														
<19 db/A	0,75	96														
<19 db/A	0,75	75														
 <p><b>ALEXA LF</b> 7,8 kg / 17,2 lbs (3)</p>	5° – 358° electronic shutter	2.39:1 16:9 Open Gate	<table border="1"> <tr> <td>&lt;20 db/A</td> <td>0,75</td> <td>150</td> </tr> <tr> <td>&lt;20 db/A</td> <td>0,75</td> <td>90</td> </tr> <tr> <td>&lt;20 db/A</td> <td>0,75</td> <td>90</td> </tr> </table>	<20 db/A	0,75	150	<20 db/A	0,75	90	<20 db/A	0,75	90	YES YES YES			
<20 db/A	0,75	150														
<20 db/A	0,75	90														
<20 db/A	0,75	90														

(1) camera body & SxS Module (2) 60-120 fps via ALEXA High Speed License K2.72076.0 (3) camera body & recording module