

ARRI JUNIOR LAMPHEADS

TECHNICAL DATA



ARRI Junior Lamphead	ARRI 150	ARRI 300 Plus	ARRI 650 Plus
Ident-No.	L0.79360.B (MAN)*	L0.79200.B (MAN)*	L0.79400.B (MAN)* L0.79400.I (P.O.)*

*incl. 4-leaf barndoor and filter frame

Main Features			
Type of Lamphead	Fresnel	Fresnel	Fresnel
Reflector	Spherical specular high purity aluminium	Spherical specular high purity aluminium	Spherical specular high purity aluminium
Wattage	150 W	300 W	650 W
Lamp Type	150 W / GX6.35 (240 V) 150 W / GX6.35 (120 V) 100 W / GX6.35 (240 V)	CP/81 FSL 300 W / GY9.5 (230 V) CP/81 FKW 300 W / GY9.5 (120 V)	CP/89 FRL 650 W / GY9.5 (120 V) CP/89 FRK 650 W / GY9.5 (120 V) CP/82 500 W / GY9.5 CP/81 300 W GY9.5
Lamp Base	GX6.35	GY9.5	GY9.5
Lens Diameter	50 mm / 1.9"	80 mm / 3.2"	112 mm / 4.5"
Color	blue/silver	blue/silver	blue/silver
Further versions	also available in Schuko, 120 V version and with line dimmer	also available in Schuko, as 120 V version as well as in color version black	also available in Schuko as 120 V version as well as in color version black

Technical Data of the Luminaire			
Max. Operating Temperature	ta= 45° C / 113° F	ta= 45° C / 113° F	ta= 45° C / 113° F
Max. Surface Temperature	tc= 200° C / 392° F	tc= 200° C / 392° F	tc= 200° C / 392° F
Tolerable Inclination	max. 90° upwards / max. 90° downwards	max. 80° upwards / max. 80° downwards	max. 80° upwards / max. 80° downwards
Safe Distances	0.9 m / 2.9 ft. to illuminated surface 0.5 m / 1.6 ft. around the luminaire	1.0 m / 3.3 ft. to illuminated surface 0.5 m / 1.6 ft. around the luminaire	1.5 m / 4.9 ft. to illuminated surface 0.5 m / 1.6 ft. around the luminaire
Protective Class	I - Protective Earth	I - Protective Earth	I - Protective Earth
Protective Rate	IP20	IP20	IP20

Specifications			
Dimensions (incl. flange) (H x W x L)	194 x 133 x 161 mm / 7.7 x 5.3 x 6.3"	269 x 189 x 158 mm / 10.6 x 7.4 x 9.5"	305 x 221 x 190 mm / 12.0 x 8.7 x 7.5"
Packed Size (H x W x L)	145 x 175 x 280 mm / 5.8 x 6.9 x 11.1"	275 x 190 x 240 mm / 10.9 x 7.5 x 9.5"	295 x 220 x 255 mm / 11.7 x 8.7 x 10.1"
Weight	approx. 1.6 kg (3.33 lbs)	approx. 2.0 kg (4.33 lbs)	approx. 2.6 kg (5.56 lbs)
Packed Weight	approx. 1.7 kg (3.75 lbs)	approx. 2.3 kg (4.94 lbs)	approx. 3.0 kg (6.44 lbs)
Mounting	Socket 16 mm / 5/8"	Socket 16 mm / 5/8"	Socket 16 mm / 5/8"
Certification	CE, UKCA, CB, ENEC, cNRTLus	CE, UKCA, CB, ENEC, cNRTLus	CE, UKCA, CB, ENEC, cNRTLus

Accessories			
Accessory diameter	78 mm (3.1")	130 mm (5.1")	168 mm (6.6")
	<ul style="list-style-type: none"> 4-leaf barndoor Filter frame Scrim Snoot 	<ul style="list-style-type: none"> 4-leaf barndoor Filter frame Scrim Chimera Lightbank Speed ring circular Snoot 	<ul style="list-style-type: none"> 4-leaf barndoor 8-leaf barndoor Filter frame Scrim Chimera Lightbank Speed ring circular Snoot

Photometrical Data			
Distance	1 m (3 ft.) [Output / diameter]	1 m (3 ft.) [Output / diameter]	1 m (3 ft.) [Output / diameter]
Spot	14.0°: 4,104 lux / Ø 0.25 m	15.0°: 16,803 lux / Ø 0.26 m	13.0°: 52,750 lux / Ø 0.23 m
Medium	30.0°: 1,899 lux / Ø 0.54 m	30.0°: 9,000 lux / Ø 0.54 m	30.0°: 22,750 lux / Ø 0.54 m
Flood	44.0°: 1,503 lux / Ø 0.81 m	55.0°: 4,500 lux / Ø 1.04 m	54.0°: 10,750 lux / Ø 1.02 m
Distance	3 m (10 ft.) [Output / diameter]	3 m (10 ft.) [Output / diameter]	3 m (10 ft.) [Output / diameter]
Spot	14.0°: 456 lux / Ø 0.74 m	15.0°: 1,867 lux / Ø 0.79 m	13.0°: 5,861 lux / Ø 0.68 m
Medium	30.0°: 211 lux / Ø 1.61 m	30.0°: 1,000 lux / Ø 1.61 m	30.0°: 2,528 lux / Ø 1.61 m
Flood	44.0°: 167 lux / Ø 2.42 m	55.0°: 500 lux / Ø 3.12 m	54.0°: 1,194 lux / Ø 3.06 m
Distance	5 m (16 ft.) [Output / diameter]	5 m (16 ft.) [Output / diameter]	5 m (16 ft.) [Output / diameter]
Spot	14.0°: 164 lux / Ø 1.23 m	15.0°: 672 lux / Ø 1.32 m	13.0°: 2,110 lux / Ø 1.14 m
Medium	30.0°: 76 lux / Ø 2.68 m	30.0°: 360 lux / Ø 2.68 m	30.0°: 910 lux / Ø 2.68 m
Flood	44.0°: 60 lux / Ø 4.04 m	55.0°: 180 lux / Ø 5.21 m	54.0°: 430 lux / Ø 5.10 m

All specifications are nominal / typical values.



For light output at any distance use our ARRI Photometrics App.

Please visit our website for downloads and to find more information about the Fresnel Tungsten: www.arri.com

